

LOAD KING 503-554-SS-SF SIGNATURE SERIES TRAILER

55-TON HYDRAULIC DETACHABLE GOOSENECK 18" LOADED DECK HEIGHT, STINGER BAR & FLIP AXLE CAPABILITIES



SPECS

GENERAL:

110,000 LB. CAPACITY IN 12' LOAD CONCENTRATION W/ STINGER
100,000 / 80,000 PSI YIELD STEEL MAIN BEAMS
EST. WEIGHT: 21,600 LBS. W/26 FT. DECK AND 53 FT. O/A LENGTH

GOOSENECK:

HYDRAULIC NON-GROUND BEARING LO-PRO SCRAPER NECK
TAPERED FRONT TO AVOID DAMAGE TO AIR, ELECTRIC & HYDRAULIC FITTINGS
12'-9" GOOSENECK

SWING CLEARANCES OF 86", 110"

AIR-ACTIVATED SELF-LOCKING PIN ON GOOSENECK, "POSITIVE SAFETY LOCK"
FULLY RECESSED AIR & ELECTRICAL HOOK-UP

DECK:

4 FULL DEPTH 16 IN. CAMBERED DECK BEAMS 26' - DECK LENGTH

30" DOUBLE HINGED HEAVY DUTY FLIP RAMPS
13 PAIR CHAIN SLOTS IN OUTER FLANGES

18" LOADED DECK HEIGHT

2" NOMINAL APITONG DECKING SECURED WITH CARRIAGE BOLTS & CLIPS FULLY BOXED BEAM IN FRONT RAMP APPROACH -

W/INTEGRATED CLEARANCE LIGHT & FLAG HOLDER

13 PAIR - FULL DEPTH OUT-RIGGERS WITH SPRING LOADED RETAINER CLIPS WIDE LOAD PACKAGE - INSIDE GUSSET FROM CROSSMEMBERS TO 0/S BEAM WEB -

& FLANGES TO PREVENT DEFLECTION IN O/S WEB WHEN UTILIZING OUTRIGGERS

6 PAIR BENT D-RINGS ON EACH SIDE

60" PIERCED PLATE IN FRONT DECK AREA FOR CHAIN & BINDER STORAGE
96" BUCKET WELL AT REAR DECK WITH PIERCED PLATE, OFFERING MAXIMUM CLEARANCE

SUBFRAME:

FRAME REINFORCING FOR FUTURE STINGER & FLIP AXLE (4 AXLES TOTAL)

AIR LIFT 3RD AXLE W/3 POSITION MANUAL RAISE & LOWER VALVE –

AVOIDS SUSPENSION DAMAGE WHEN RAISE & LOWER VALVE IS LEFT IN REGULATED POSITION

27,500 LB. AXLES – 5" X 3/4" WALL

3RD TAIL LIGHT W/STROBES & 4-WAY PLUG - ALL LED LIGHTS REAR MARKER LIGHTS ARE DUAL INTENSITY
RE-DESIGNED REAR TAILGATE - DESIGNED TO ALLOW THE OPERATOR TO EASILY WORK ALL CONTROLS AND ADD ADDITIONAL AXLES
FIRESTONE TIRES







833 - CT - SPECS wwww.customtruck.com



^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.