



# NATIONAL CRANE 9103A 26-TON BOOM TRUCK TO 103'



# SPECS

103' 4-SECTION BOOM, REAR MOUNT INSTALLATION  
DUAL CONTROL STATIONS  
DUAL ENGINE THROTTLE ENGINE START / STOP  
AVAILABLE ON MANY DIFFERENT CHASSIS MAKES, MODELS  
LOAD MOMENT SYSTEM W/ INTERNAL WIRE A2B  
BURST OF SPEED WINCH  
BARE DRUM PULL - 10,200 LBS.  
375 DEGREE NON-CONTINUOUS ROTATION  
STRONGER, FULL LENGTH TORSION BOX  
A-FRAME MAIN OUTRIGGERS  
OUTRIGGER MONITORING SYSTEM  
SINGLE REAR STABILIZER  
340' 9/16" ROTATION RESISTANT WIRE ROPE  
SINGLE LINE PULL 7,700 LBS.  
OPEN CENTER HYDRAULICS  
66 GAL. HYDRAULIC RESERVOIR  
7 TON HEADACHE BALL  
SPEEDY-REEVE BOOM TIP & SHEAVE BLOCKS  
PBR-R BOOM REST  
[-9 TO +80 DEGREE] BOOM ELEVATION  
EASY GLIDE BOOM WEAR PADS  
CONTROL KNOB ON SWING MOTOR BRAKE RELEASE  
VALVE-ADJUSTS TO SWING SPEED PREFERENCE  
BEARINGS ON BOOM & RETRACT CABLES-GREASED THROUGH ACCESS HOLES  
IN SIDE PLATES  
COMPONENTS PAINTED PRIOR TO ASSEMBLY  
EASY-TO-REMOVE WINCH



833 - CT - SPECS  
[www.customtruck.com](http://www.customtruck.com)

\*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

