



NATIONAL CRANE 9125A 26-TON BOOM TRUCK TO 125'



SPECS

125' (5 SECTION) BOOM
AVAILABLE ON MANY DIFFERENT CHASSIS MAKES, MODELS
REAR MOUNT INSTALLATION
DUAL CONTROL STATIONS
HYDRAULIC CAPACITY ALERT WITH INTERNAL WIRE
A2B
BURST-OF-SPEED WINCH
375 DEGREE NON-CONTINUOUS ROTATION
18' STEEL FLATBED
A-FRAME MAIN OUTRIGGERS
OUT/DOWN AUX OUTRIGGERS (MOUNTED OVER FRAME)
CENTER REAR OUTRIGGERS
9/16" ROTATION RESISTANT ROPE
LOAD BALL W/SWIVEL HOOK
1 SHEAVE LOAD BLOCK
TRIPLE PUMP HYDRAULICS
HOT SHIFT PTO



833 - CT - SPECS
www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

