

## NATIONAL CRANE NBT40-142 40-TON BOOM TRUCK

TO 142'



## **SPECS**

142' 5-SECTION FULL POWER BOOM
190' MAX. TIP HEIGHT (W/ JIB)
AVAILABLE ON MANY DIFFERENT CHASSIS MAKES, MODELS
OPT. 31'-55' FOLDAWAY JIB FOR 205' VERTICAL REACH
150' MAX. TIP HEIGHT (MAIN BOOM)
40 US TON RATING

PILOT-OPERATED HYDRAULIC CONTROLLERS
SELF-LUBRICATING EASY GLIDE WEAR PADS
CAPACITY CHARTS FOR 100%, 50% & FULLY RETRACTED OUTRIGGERS
LMI W/ GRAPHICAL DISPLAY, LCD DISPLAY VISIBLE IN FULL/LOW LIGHT
WORK AREA DEFINITION SYSTEM
STRONGER STANDARD TORSION BOX
1,900 LBS. TAILSWING COUNTERWEIGHT
AVAILABLE WITH OPTIONAL WORK PLATFORM

TWO-SPEED GROOVED DRUM HOIST W/ CABLE PACKER, ELECTRONIC DRUM ROTATION INDICATOR

WELL-INSULATED DELUXE OPERATOR'S CAB W/ DIESEL HEATER,
DEFROSTER & SKYLIGHT, RIGID GALVANNEALED STEEL STRUCTURE,
TINTED SAFETY GLASS, MULTI-POSITION SEAT W/ ARM REST-MOUNTED SINGLE AXIS CONTROLS,
VENTILATION FANS, DUAL CAB MOUNTED WORK LIGHTS

BEARINGS ON BOOM & RETRACT CABLES CAN BE GREASED THROUGH ACCESS HOLES IN BOOM SIDE PLATES

BOOM SECTIONS SUPPORTED BY ONE HYDRAULIC EXTEND CYLINDER

STATE-OF-THE-ART CONTROL VALVE

PAINTED PRIOR TO ASSEMBLY

SPEEDY-REEVE BOOM TIP & SHEAVE BLOCKS







833 - CT - SPECS wwww.customtruck.com



<sup>\*</sup>Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.