



# TORO RT1200 RIDING TRENCHER WITH 48.5 GPM MAXIMUM PUMP CAPACITY





# SPECS

ATTACHMENT PUMP CAPACITY: 48.5 GPM MAX.  
AUXILIARY PUMP RELIEF: 2,750 PSI  
COOLING SYSTEM: LIQUID COOLED  
ENGINE: CUMMINS QSB 4.5 DIESEL  
GROUND DRIVE PUMP CAPACITY: 48.5 GPM (134.8 L/M)  
HYDRAULIC OIL CAPACITY: 40 GALLONS (151 LITERS)  
TIRES: 38 X 18-20, 12-PLY  
TRANSMISSION: 4-SPEED SHIFT ON-THE-FLY HYDROSTATIC  
AUXILIARY PUMP CAPACITY: 48.5 GPM PER PORT  
AXLE TYPE: LOCKING DIFFERENTIAL, OUTBOARD PLANETARY  
DIMENSIONS: 159.6" X 85.8" X 110.4"  
FUEL CAPACITY: 48 GALLONS (182 LITERS)  
GROUND DRIVE PUMP RELIEF PRESSURE: 5,365 PSI (420 BAR)  
MAXIMUM CREEP SPEED: 1.2 MPH  
TRACK: 18.5" WIDE  
TRANSPORT SPEED: 10.2 MPH FWD, 7.1 MPH REV.

CUMMINS® 4.5 LITER, 121 HP ENGINE DELIVERS ADDED POWER FOR FASTER, MORE PRODUCTIVE TRENCHING

TOOL CARRIER CHASSIS DESIGN ALLOWS THE RT1200 TO BE CONFIGURED FOR EACH SPECIFIC JOB; CHOOSE FROM TRACKS OR TIRES, AND SEVERAL DIFFERENT ATTACHMENTS, INCLUDING BACKHOE, ROCKSAW, VIBRATORY PLOW, REEL CARRIER, AND TRENCHER DRIVE

OPEN-DESIGN OPERATOR PLATFORM AND TRACTION AND ATTACHMENT CONTROLS MOUNTED TO OPERATOR'S SEAT ALLOW FOR MAXIMUM JOBSITE VISIBILITY FROM ANY ANGLE

ATTACHMENTS:  
**BACKFILL BLADE**

WIDTH: 83.1"  
HEIGHT: 17.7"

LIFT HEIGHT (ABOVE GRADE) W/ TIRES: 21"  
BLADE DROP (BELOW GRADE) W/ TIRES: 7.1"  
LIFT HEIGHT (ABOVE GRADE) W/ TRACKS: 24"  
BLADE DROP (BELOW GRADE) W/ TRACKS: 4.1"  
MAXIMUM SWING ANGLE: 30 DEGREES  
TILT ANGLE: 6 DEGREES

**P105 VIBRATORY PLOW**

LENGTH (MINIMUM, TRANSPORT): 82"  
HEIGHT (TRANSPORT): 105"  
WEIGHT: 3,125 LBS.  
MAXIMUM DEPTH: 36"  
PILOT SWING ANGLE: 30"  
PLOW STEER ANGLE: 30"

PLOW BLADE ATTITUDE ADJUSTMENT: 32 DEGREES

**HEAVY DUTY TRENCHER**

LENGTH (MINIMUM, TRANSPORT, 4' BOOM): 96.8"  
WEIGHT: 1,468 LBS.  
DIGGING CHAIN SPEED: 669 FT/MIN  
MAXIMUM DEPTH: 84"  
WIDTH (MAXIMUM/MINIMUM): 18" / 7"

**REEL CARRIER**

CAPACITY: 2,500 LBS. REEL  
WEIGHT W/ COUNTERWEIGHT: 6,500 LBS.

**762 HD BACKHOE**

HEIGHT (TRANSPORT): 122"  
WEIGHT (W/ 18" BUCKET): 3,029 LBS.  
MAXIMUM REACH: 163"  
MAXIMUM DIGGING DEPTH: 111.6"



833 - CT - SPECS  
[www.customtruck.com](http://www.customtruck.com)

\*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

