



# TORO RT600 RIDING TRENCHER WITH 35.6 GPM MAXIMUM PUMP CAPACITY





# SPECS

ATTACHMENT PUMP CAPACITY: 35.6 GPM MAX.  
AUXILIARY PUMP RELIEF: 2,500 PSI  
COOLING SYSTEM: LIQUID COOLED, 4.5 GAL. (17L) CAPACITY  
ENGINE: CUMMINS B3.3  
GROUND DRIVE PUMP CAPACITY: 35.6 GPM (134.8 L/M)  
HYDRAULIC OIL CAPACITY: 19 GALLONS (72 LITERS)  
TIRES: 31 X 15.50-15, 8-PLY  
AUXILIARY PUMP CAPACITY: 6.5 GPM PER PORT  
(25 L/M, 2 PORTS ON PUMP)  
AXLE TYPE: (FRONT/REAR) STEERABLE PLANETARY  
DIMENSIONS: LENGTH: 128.3"; WIDTH: 72"; HEIGHT: 96";  
WEIGHT: 6,350 LBS.; GROUND CLEARANCE: 7.4"  
FUEL CAPACITY: 20 GALLONS (72 LITERS)  
GROUND DRIVE PUMP RELIEF PRESSURE: 5,000 PSI (345 BAR)  
MAXIMUM CREEP SPEED: 1.4 MPH  
TRANSPORT SPEED: 6.2 MPH (FWD), 4.6 MPH (REV.)  
INLINE HYDROSTATIC GROUND AND ATTACHMENT DRIVE SYSTEM PROVIDE  
OPTIMAL PERFORMANCE FOR TRENCHING AND PLOWING  
STANDARD FOUR-WHEEL STEERING WITH PLANETARY AXLES USING CONSTANT  
VELOCITY U-JOINTS MAKES GETTING INTO TIGHT SPACES EVEN EASIER



833 - CT - SPECS  
[www.customtruck.com](http://www.customtruck.com)

\*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

