



LOAD KING 252CS STEPDECK TRAILER

with 50,000 LB. CAPACITY



SPECS

DIMENSIONS:
CAPACITY: 50,000 LB. - EVENLY DISTRIBUTED
OVERALL LENGTH: 38'2"
GOOSENECK: 10'3"
DECK LENGTH: 18'
DECK WIDTH: 102"
DECK HEIGHT: 32.5" LOADED
SUBFRAME: 6'11"
BEAVERTAIL: 3'
WEIGHT: 10,900 LBS.

GOOSENECK:
NARROW
48" KINGPIN HEIGHT
79" SWING CLEARANCE
15" KINGPIN SETTING
CHAIN TRAY BETWEEN MAIN BEAMS
LANDING GEAR: 4-POSITION DROP LEG

DECK:
CENTER BEAM FRAME DESIGN
SIDE RAIL: STRUCTURAL CHANNEL - 20.7LB. PER FT.
CROSSMEMBERS: 10' WIDE FLANGE ON 30" CENTERS
2" NOMINAL OAK SECURED WITH 5/16" SCREWS

SUBFRAME:
AXLES: (2) 22,500 LB. OIL BATH
SUSPENSION: HUTCH 9,700-44,000 LB. CAPACITY
TIRES: (8) 215/75R17.5 RADIALS (H)
WHEELS: 8-HOLE STEEL DISC - HUB-PILOTED
BRAKES: 12.25" X 7.5" DRUM STYLE AIR BRAKES
ABS: WABCO 2S1M
OPEN WELL WHEELS

REAR LOADING:
BEAVERTAIL: 15 DEGREE LOAD ANGLE
RAMPS: 60" X 22.5" SPRING-ASSISTED
SURFACE: OAKWOOD DECKING



833 - CT - SPECS
www.customtruck.com



*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL