



AQUATECH B10

COMBINATION CLEANING MACHINE



SPECS

AIR/VAC SYSTEM:
POSITIVE DISPLACEMENT EXHAUSTER
2700 CFM OPERATING CAPACITY
204" WATER COLUMN
POLY CHAIN DRIVE
PROTECTED BY MICRO-FILTER/CENTRIFUGAL SEPARATOR
VACUUM RELIEF VALVES

TANK:
CYLINDRICAL DESIGN
10 CU. YD.
DUMPING 45 DEGREES
HYDRAULIC POWER UP/DOWN CYLINDER
SELF ALIGNING CLOSURE SEAL
TOP-HINGED FULL OPENING REAR DOOR
TWO 5" LIQUID LEVEL SIGHT EYES
DEBRIS DEFLECTOR PLATE
DOUBLE STRAINER FOR REAR DOOR DRAIN
REAR DOOR SECURITY PROP

BOOM:
TOP MOUNTED
360 DEGREE ROTATION
PORTABLE PENDANT, CONTROLS ALL FUNCTIONS
INTERNAL BOOM VALVE
8" EXTRA HEAVY DUTY RUBBER INTAKE HOSE
EXTENDS TO 20'
POWERS UP/DOWN
REAR STORAGE LOCATION
QUICK OPEN CLEANOUT

WATER SYSTEM:
TRIPLEX RECIPROCATING
80 GPM
2500 PSI
POLY CHAIN DRIVE
PRESSURE RELIEF VALVE
WATER FLOW CONTROL VALVE
AIR VALVE ON PUMP FOR COLD WEATHER OPERATION
WAS DOWN GUN CONNECTION
WAS DOWN GUN WITH 35' OF 1/2" HOSE



888-925-0858
www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

