

CONDUX TESMEC PT1250

HYDRAULIC PULLER-TENSIONER



SPECS

PULLER PERFORMANCE

MAX PULL: 11,240 LBF (50 KN)

SPEED AT MAX PULL: .9 MPH (1,5 KM/H)

MAX SPEED: 3.1 MPH (5 KM/H)

PULL AT MAX SPEED: 3,597 LBF (16 KN)

NOTE: THE BASIC MACHINE PERFORMANCE IS CALCULATED AT 68°F (20°C) AND AT SEA LEVEL

CHARACTERISTICS

BULL-WHEEL DIAMETER: 59 IN (1,500 MM)

MAX CONDUCTOR/ROPE DIAMETER: 1 5/8 IN (42 MM)

NET WEIGHT: 9,700 LBS (4,400 KG)

NUMBER OF GROOVES: 6

ENGINE

DIESEL: 74 HP (55,4 KW)

EMISSION LEVEL: TIER 4F/STAGE IIIIB

COOLING SYSTEM: WATER

ELECTRICAL SYSTEM: 12 V

HYDRAULIC TRANSMISSION

CLOSED HYDRAULIC WITH A PULL PRESETTING SYSTEM THAT

AUTOMATICALLY ADJUSTS PULLING SPEED







888-925-0858 www.customtruck.com



^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.