



# CONDUX TESMEC AFS303 PULLER-TENSIONER

WITH 5,600 LB. TENSIONING CAPACITY





# SPECS

## PULLER PERFORMANCE:

5,600 LBF MAX PULL  
1.6 MPH @ MAX PULL  
2.6 MPH MAX SPEED

## TENSIONER PERFORMANCE:

5,600 LBF MAX TENSION  
3.1 MPH MAX SPEED

## CHARACTERISTICS:

59" BULLWHEEL DIAMETER  
1 7/16" MAX CONDUCTOR DIAMETER  
3/8" MAX ROPE DIAMETER  
5,071 LBS WEIGHT

## ENGINE:

46 HP DIESEL ENGINE  
WATER COOLING SYSTEM  
12V ELECTRICAL SYSTEM

## HYDRAULIC TRANSMISSION:

CLOSED HYDRAULIC CIRCUIT  
STEP-LESS SPEED VARIATION, BOTH DIRECTIONS  
PULL PRE-SETTING SYSTEM

## STANDARD EQUIPMENT:

NEGATIVE SELF-ACTING HYDRAULIC BRAKE  
HYDRAULIC OIL COOLING SYSTEM  
HYDRAULIC ROPE/CONDUCTOR CLAMP  
HYDRAULIC QUICK CONNECTORS

ELECTRONIC ADAPTER FOR CONNECTION OF MULTIPLE MACHINES AND FOR STRINGING SYNCHRONIZATION

DIGITAL METER COUNTER

CONTROL INSTRUMENTS FOR HYDRAULIC SYSTEM AND DIESEL ENGINE  
RIGID AXLE FOR TOWING AT MAX SPEED OF 19 MPH W/ MECHANICAL PARKING BRAKE

GEARBOX W/ 3 OPERATING POSITIONS:

- NEUTRAL
- LOW TENSION (225-1,125 LBF)
- NOMINAL TENSION (1,125 LBF- 5,600 LBF)

HYDRAULICALLY ACTUATED FRONT PLOUGH STABILIZER  
GROUNDING CONNECTION POINT

## GENERAL SPECIFICATIONS:

7,250 LB. NET WEIGHT  
183" OVERALL LENGTH  
84" OVERALL WIDTH  
105" HEIGHT



888-925-0858  
[www.customtruck.com](http://www.customtruck.com)



\*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL