

CONDUX TESMEC PT2450

HYDRAULIC PULLER-TENSIONER



SPECS

PERFORMANCE

MAX PULL: 2 X 11,240 LBF (50 KN)/1 X 22,480 LBF (100KN) SPEED AT MAX PULL/TENSION: 1.25 MPH (2 KM/H)

MAX SPEED: 3.1 MPH (5 KM/H)

PULL/TENSION AT MAX SPEED: 2 X 4,500 LBF (20 KN)

NOTE: THE BASIC MACHINE PERFORMANCE IS CALCULATED AT 68°F (20°C) AND AT SEA LEVEL.

CHARACTERISTICS

BULL-WHEEL DIAMETER: 59 IN (1,500 MM)

MAX CONDUCTOR/ROPE DIAMETER: 1 5/8 IN (42 MM)

WEIGHT: 20,100 LBS (9,120 KG)

NUMBER OF GROOVES: 12

ENGINE

DIESEL: 140 HP (105 KW)
EMISSION LEVEL: TIER 4F/STAGE IV
COOLING SYSTEM: WATER
ELECTRICAL SYSTEM: 24 V
HYDRAULIC TRANSMISSION

CLOSED HYDRAULIC WITH A PULL PRESETTING SYSTEM THAT AUTOMATICALLY ADJUSTS PULLING SPEED.







888-925-0858 www.customtruck.com



^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.