



ELLIOTT E160 TRACKED BUCKET

160' A92.2-CERTIFIED AERIAL WORK PLATFORM
ON CTRAC8000 CRAWLER CARRIER



SPECS

160' WORKING HEIGHT
215' W/ JIB
HYDRAULIC TOOL CIRCUIT W/ INTENSIFIER
5-SECTION FULLY
PROPORTIONAL MAIN BOOM
360 DEGREE WORKING AREA
30,000 LBS. LIFT CAPACITY
36" X 72" 2-MAN PLATFORM W/ CAPACITY: 1,200 LBS.

JIB LENGTHS: 32-55'
ANSI A92.2 CERTIFICATION
12'11" OAH
RIDE-AROUND SEATED OPERATOR CONTROLS
AMSTEEL BLUE SYNTHETIC ROPE
OUT-DOWN EZ CRIB OUTRIGGERS
WIRELESS RADIO REMOTE CONTROLS W/ INTEGRAL LMI DISPLAY
GREER INSIGHT FULL COLOR LMI SYSTEM
HEAVY DUTY SUBFRAME - FULL-LENGTH
OVERSIZED ROTATION BEARING AND GEARBOX
RUGGED BOOM DESIGN

CTRAC8000:

VERSATILE, HIGH PAYLOAD, LOW GROUND PRESSURE TRACK VEHICLE
SPECIALLY DESIGNED TO DELIVER TODAY'S GENERATION OF HIGH CAPACITY CRANES &
LONG-REACHING PLATFORMS TO THOSE JOBSITES YOU CAN'T REACH ON RUBBER TIRES.
ITS UNIVERSAL CHASSIS DESIGN MAKES FOR EASY MOUNTING AND DISMOUNTING BETWEEN EQUIPMENT.
THE CRANE OR LIFT MOUNTED TO THE CTRAC8000 WILL SEE NO CHANGE IN THE STANDARD LIFT CAPACITIES, CHARTS OR RANGE DIAGRAMS
THERE ARE NO MODIFICATIONS TO THE OUTRIGGERS OR CRITICAL COMPONENTS, MAINTAINING THE MANUFACTURER'S WARRANTY
STANDARD TIER 4 CUMMINS ENGINE IS COMPLIANT WITH ALL US EMISSIONS STANDARDS
EXPORT ENGINES AVAILABLE
DUAL BOGIE WHEELS MAXIMIZE STABILITY, MAINTAIN EVEN GROUND PRESSURE & IMPROVE LATERAL STABILITY
ACCEPTS ANY CRANE/AERIAL DEVICE/TRUCK-MOUNTED EQUIPMENT REQUIRING AN 80K GVWR CHASSIS



888-925-0858
www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

