

GEHL RS12-42 TELEHANDLER

WITH 12,000 LBS. CAPACITY



SPECS

PERFORMANCE

PROVEN WELDED BOX-SECTION BOOM DESIGN

CYLINDER DESIGN PROVIDES ONE OF THE FASTEST CYCLE TIMES IN THE INDUSTRY

STRONG FRAME WITH REINFORCED C-CHANNELS PERFORMS

FRAME LEVELING FEATURE ADJUSTS 10-DEGREES TO THE LEFT AND RIGHT

INTERNAL WET DISC BRAKES PROVIDE EXCELLENT STOPPING ABILITY AND LONG LIFE

DUAL-ELEMENT AIR FILTER PROTECTS THE ENGINE FROM AIRBORNE CONTAMINANTS

OPERATOR'S CABIN: 44 CUBIC-FOOT CAB ENCLOSURE PROVIDES OPTIMAL LEG ROOM

SPACIOUS OPERATING ENVIRONMENT
ROPS/FOPS CANOPY IS STANDARD EQUIPMENT
ROPS/FOPS ENCLOSED CAB IS OPTIONAL
FOPS IS COMPLETELY WELDED INTO THE ROPS
VIRTUALLY 360-DEGREE VISIBILITY INCREASES SAFETY AND OPERATING ACCURACY
DELUXE HIGH-BACK SEAT MAXIMIZES OPERATOR COMFORT
ADJUSTABLE SUSPENSION SEAT IS OPTIONAL
SIDE AND REAR GLASS IS STANDARD EQUIPMENT, ENHANCING OPERATOR SAFETY

HANDLING

THREE STEERING MODES – 4-WHEEL, 2-WHEEL AND CRAB
STEERING MODES EASILY CHANGED BY THE FLIP OF A SWITCH
SAHR PARKING BRAKE IS APPLIED AUTOMATICALLY (@ ENGINE OFF)

ENGINE

JOHN DEERE 4045T INTERIN TIER IV 115 HP

19.3MPH MAX. TRAVEL SPEED

2500 RPM SPEED RATING







888-925-0858 www.customtruck.com



^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.