



# HOGG & DAVIS HYDRA 985 UNDERGROUND PULLER

PULLS UP TO 24,000 LBS. "BARE DRUM"





# SPECS

LINE PULL:  
PULLS UP TO 24,000 LBS., "BARE DRUM"  
FRICTION DRIVE SYSTEM  
INDEPENDENT DRIVE ROLLER HOUSINGS  
CENTER MOUNTED POWER UNIT  
FOUR-ROLLER CONTACT AT ALL TIMES

MAIN FRAME:  
FULLY BOXED & REINFORCED, OPEN YOKE  
20,000 LB. STUB SPINDLE AXLE  
FULL AIR BRAKES W/ ABS  
14/80R20 TIRES  
MULTI-POCKET VERTICAL LIFT HYDRAULIC MANDREL RACKS  
UNIFORM GROUND CLEARANCE & LOW CENTER OF GRAVITY  
2 1/2" HEAT TREATED REEL MANDREL W/ CENTERING CONES & LOCKING COLLARS  
HYDRAULIC DRAWBAR W/ LOAD LOCKED CYLINDER  
HYDRAULIC IDLER WHEEL W/ PNEUMATIC TIRE, ANTI-ACTIVATION VALVES

ENGINE SPECIFICATIONS:  
JOHN DEERE MODEL 3015 D  
3 CYLINDERS  
33 HP @ 3000 RPM  
LOW OIL PRESSURE & ENGINE PRE-HEAT INDICATOR LIGHTS  
BLOCK HEATER

DIMENSIONS:  
LENGTH: 197"  
WIDTH: 94"  
HEIGHT: 80"  
APPROXIMATE WEIGHT: 6,500 LBS.

MAIN CONTROL PANEL:  
LOCATED FRONT, CURBSIDE  
CONTAINS ALL ENGINE & PULLING CONTROLS & ASSOCIATED GAUGES  
PROPORTIONAL PULLING CONTROL

REAR CONTROL PANEL:  
LOCATED REAR, CURBSIDE  
OFFER CLEAR VISIBILITY FOR UNDERGROUND PULLING OPERATION



888-925-0858  
[www.customtruck.com](http://www.customtruck.com)

\*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

