



SPECS

PERFORMANCE

CONTINUOUS LINEPULL RATING: 10,000 LBS
CONTINUOUS TORQUE RATING: 200,000 IN-LB
INFINITELY VARIABLE SPEED FROM 0.0 – 4.2 MPH

DRUM CAPACITY

RATED DIAMETER: 80"
WIDTH: 57.5"
RATED ROPE CAPACITY: 20,000 FEET (1" DIA.)

DRIVE SYSTEM

JOHN DEERE 185.0 HP @ 2,400 RPM TEIR IV DIESEL ENGINE
CLOSED LOOP HYDRASTATIC HYDRAULIC DRIVE
SPRING APPLIED, HYDRAULIC RELEASE DRIVE TRAIN BRAKE
MECHANICAL CLUTCH ON DRIVE HUB ENGAGEMENT
STANDARD FREEWHEEL DISCONNECT ON DRIVE HUB
36" DIA. MEDIUM CARBON OVERSPIN BRAKE

UNIT DIMENSIONS

LENGTH: 19'6"
WIDTH: 8'5"
HEIGHT: 9'7"
2690 LB TONGUE WEIGHT
WEIGHT (WITH ROPE AND FLUIDS): 23,010 LBS

TRAILER DATA

TANDEM 15,000 LB LEAF-SPRUNG AXLES
26,000 LB GVWR
ELECTRIC TRAILER BRAKES
(3) DROP-LEG MANUAL LEVELING JACKS
(4) R19.5 – 16 PLY RATED TIRES
FULL COVERAGE FENDERS WITH MUDFLAPS
D.O.T. LED TRAILER LIGHTING WITH 7-WIRE CONNECTOR

GENERAL FEATURES

20.1 GALLON FUEL TANK W/LEVEL GAUGE
33 GALLON HYDRAULIC OIL TANK
HYDRAULIC BOOM LEVELWIND
LOCKABLE STEEL BATTERY BOX
BAKED WHITE ENAMEL FINISH



888-925-0858
www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

