



HOGG & DAVIS OLT 52B BULLWHEEL TENSIONER

OVERHEAD LINE TENSIONER



SPECS

TENSIONING DEVICE:
MULTI GROOVE BULLWHEELS
RATED AT 5000 LBS
REAR JACKSTANDS MANUAL
UNIT LENGTH 17' 11"
WIDTH 96"
TANDEM LEAF SPRING AXLES
BRAKES ELECTRIC
GAWR 16,000 LBS
TIRES 235/85/16 14 PLY
BULLWHEEL SPECIFICATIONS:
DIAMETER (WITH LINING) 54"
LINING (4) URETHANE DIAMETER MOLDED
GROOVE DIAMETER 1.5"
BRAKING HYDRAULIC

BRAKING SPECIFICATIONS:
BRAKE MATERIAL BRONZE
DIAMETER 36"
BRAKING MECHANISM HYDRAULIC
ACTUATOR CHARGE PUMP WITH ROTARY ADJUSTMENT

REEL CARRIER SPECIFICATIONS:
REEL CAPACITY: 12,000 LBS
MAXIMUM REEL: WIDTH 56"
MAXIMUM REEL: DIAMETER 96"
ANTI-OVERSPIN BRAKE 16"



888-925-0858
www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

