



HOGG & DAVIS OLT 72B BULLWHEEL TENSIONER

OVERHEAD LINE TENSIONER



SPECS

DESCRIPTION:

OLT 72 IS DESIGNED TO INSTALL SINGLE CONDUCTOR. CANTED BULLWHEELS PREVENT UNNECESSARY

TWISTING OF THE CONDUCTOR DURING INSTALLATION. REPLACEABLE DIAMETER MOLDED SEGMENTS.

MOLDING OF THE SEGMENTS IN THIS MANNER ELIMINATES THE GAPS BETWEEN SEGMENTS AND CREATES A SMOOTH CABLE SURFACE. 36" STAINLESS STEEL DISC BRAKES, WITH CENTRALIZED BRAKING CONTROLS. ADJUSTABLE FAIRLEADS FOR MULTIPLE SETUPS. FRONT TO BACK, LEFT TO RIGHT TO TOWER, AND RIGHT TO LEFT TO TOWER.

TENSIONING DEVICE:

*[2] 72" DIAMETER BULLWHEELS (WITH LINING) , 8 REPLACEABLE URETHANE MOLDED LININGS PER BULLWHEEL. (5) 2.5" GROOVES PER BULLWHEEL, 10,000 LB. TENSIONING CAPACITY

*TWO 36" DIAMETER STAINLESS STEEL DISCS PER BULLWHEEL WITH HYDRAULIC CALIPERS. CHARGE PUMP ACTUATOR WITH ROTARY ADJUSTMENT.
*CENTRALIZED FULLY HYDRAULIC OPERATOR STATION WITH PROTECTIVE SCREEN AND ADJUSTABLE SEAT.
*FRONT & REAR LARGE RUBBER ADJUSTABLE FAIRLEADS.

TRAILER:

TANDEM 7,000 LB. LEAF SPRUNG AXLES, SINGLE 235/75R17.5 TIRES, 8 BOLT RIMS, ELECTRIC TRAILER BRAKES, 7 WIRE ROUND TRAILER PLUG, ADJUSTABLE PINTLE HITCH, MANUAL TONGUE JACK, TWO REAR MANUAL JACKS, FULL COVER FENDERS. 15,000

DIMENSIONS:

17' 6" LONG
8' WIDE
10' 4" TALL (WITH FAIRLEADS OFF)
12' TALL (WITH FAIRLEADS ON)
11,000 LBS.



888-925-0858

www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

