



SPECS

ENGINE

KOMATSU SAA6D107E-2, 6-CYLINDER
4-CYCLE, WATER-COOLED, DIRECT INJECTION

168HP

HYDROSTATIC TRANSMISSION / DUAL PATH

BLADE

DOZER BLADE TYPE: 6-WAY (PAT)

BLADE WIDTH: 12'8"

BLADE HEIGHT: 45"

BLADE CAPACITY: 5 CU. YARDS

BLADE DIG DEPTH: 23"

MAX BLADE TILT, HYDRAULIC: 20"

UNDERCARRIAGE

PARALLEL LINK UNDERCARRIAGE SYSTEM

W/ LUBRICATED ROTATING BUSHINGS

TRACK SHOE WIDTHS AVAILABLE: 34"

STANDARD TRACK SHOE WIDTH: 34"

TRACK LENGTH ON GROUND: 10'5"

GROUND PRESSURE/PSI: 4.87

TRACK GAUGE: 84"

GROUND CLEARANCE: 15.6"

CUSTOM TRUCK CONFIGURATION ATTACHMENTS: SINGLE WINCHES



888-925-0858

www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

