



SPECS

DIMENSIONS

20 CUBIC YARDS STRUCK CAPACITY
60,000 LBS RATED NET PAYLOAD
13,780 LBS ESTIMATED BASE TRAILER WEIGHT
40° OVERALL LENGTH, 102" OVERALL WIDTH
108" OVERALL HEIGHT WITH SIDEBOARDS
64" X 106" HOPPER DUMP OPENING
90" X 190" UPPER HOPPER OPENING
48" 5TH WHEEL HEIGHT

FRAME 100,000/80,000 STEEL CONSTRUCTION

BOX TUBE RAIL TO PREVENT MATERIAL BUILD-UP
WOOD SIDEBOARDS WITH BRACKETS
REPLACEMENT GATE PIVOT BEARINGS
MULTIPLE POSITIONS FLEXI-SET GATE LIMITER

8" DIAMETER GATE CYLINDER WITH CHROMED TUBE AND ROD 12V SOLENOID OPERATED GATE CONTROLS

ACCESS CENTER FOR GATE AIR COMPONENTS

HOLES IN GATE ENDS FOR CHAIN STOPS
CORNER CASTINGS AT LOWER HOPPER CORNERS

SUBFRAME

AIR RIDE SUSPENSION

49" AXLE SPACING

WINDROW DEFLECTOR ON FRONT AXLE

TWO 22,500 LB AXLE CAPACITY

EIGHT 11 R 24.5 TIRES

8 OUTBOARD MOUNT HUB PILOTED BUDD TYPE DISC WHEELS TAPERED ROLLER WHEEL BEARINGS

STEMCO WHEEL SEALS WITH GRIT GUARD

RUBBER BUSHED SIDE OSCILLATING 5TH WHEEL

OIL SEALS

16 $1\!\!/_{\!2}$ INCH 7 INCH SPRING BRAKES WITH ABS SYSTEM

EXTERNAL BRAKE AIR DRAIN

FENDERS OVER REAR TANDEM

OTHER

DOT RUBBER MOUNTED SEALED LED LIGHTS WITH MODULAR HARNESS BLACK RUBBER LOAD KING MUD FLAPS, CONSPICUITY TAPE

SHOT BLAST - PRIMED AND PAINTED YELLOW POLYURETHANE

PUSH BLOCK HEAVY DUTY BOLT ON STYLE REMOTE PENDANT ON DRIVERS SIDE SWITCH AND WIRING FOR IN CAB CONTROL







833-955-7732 www.loadkingmfg.com



^{*}Load King reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.