

## LOAD KING 402-604-DD-SFF DETACHABLE GOOSENECK TRAILER

DROP DECK, with PROVISIONS FOR A STINGER OR FLIP AXLE



## **SPECS**

40 TONS IN 12 LOAD CONCENTRATION WITH 2 AXLES IG 60 MPH
60 TONS IN 12' LOAD CONCENTRATION WITH 4 AXLES IG 60 MPH
100,000/80,000 PSI YIELD STRENGTH STEEL
26,000LB ESTIMATED BASE WEIGHT
19'-6" GOOSENECK LENGTH INCLUDING 66" FLIP OVER EXTENSION
175" SWING CLEARANCE WITH 109" & 85" SWING ON BASE
GOOSENECK:

26' DECK LENGTH

24" LOADED DECK HEIGHT

8" LOADED GROUND CLEARANCE

51" 5TH WHEEL HEIGHT

HYDRAULIC NON-GROUND BEARING GOOSENECK DESIGN

RATCHET SYSTEM ENABLES MULTIPLE RIDE HEIGHTS

HYDRAULIC FRAME LIFT SUPPORT

4 FULL DEPTH 16 CAMBERED DECK BEAMS
30" FRONT FLIP RAMPS
HEAVY DUTY I-BEAM CROSSMEMBERS ON 24" CENTERS
8 D-RINGS PER SIDE
26 FULL DEPTH FABRICATED OUTRIGGERS-POWDER COAT FINISH
2" APITONG IN TRACK AREA SECURED WITH BOLTS, CLIPS, AND SCREWS
30 DEGREE RADIUS REAR DROP
34 HEIGHT REAR BOLSTER

DECK TO SUBFRAME CONNECTION: REMOVABLE WITH HORIZONTAL PIN SUBFRAME:

REINFORCING AND CONNECTIONS FOR OPTIONAL 4TH AXLE (CLOSED

AIR RIDE SUSPENSION WITH AUTO AND ADJUSTABLE HEIGHT CONTROL

54 1/2" AXLE SPACING

HUB PILOTED STEEL DISC WHEELS OUTBOARD MOUNTED DRUMS

LOAD KING MUD FLAPS
SHOT BLAST - PRIMED AND PAINTED BLACK POLYURETHANE
COMPATIBILITY:







833-955-7732 www.loadkingmfg.com



<sup>\*</sup>Load King reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.