

LOAD KING 403-4 DFMR RAIL TRAILER

DROP DECK MECHANICAL FOLDING GOOSENECK



SPECS

SUBFRAME:

THREE (3) FIXED 25,000 LB AXLES
AIR RIDE SUSPENSION WITH AUTO AND ADJUSTABLE HEIGHT CONTROL

54" AXLE SPACING

TWELVE (12) 235/75R17.5 RADIAL TIRES

HUB PILOTED STEEL DISC WHEELS

OUTBOARD MOUNTED BRAKE DRUM WITH ABS

12 1/4" X 7 1/2" SPRING BRAKES WITH REMOTE DRAINS

COVERED WHEELS WITH GROUSER BARS

CENTER SUBFRAME COVERED

DIMENSIONS:

MECHANICAL FOLDING GOOSENECK - RAILROAD SPEC

40 TONS IN 16' LOAD CONCENTRATION

100,000/80,000 PSI YIELD STRENGTH STEEL

22,200# ESTIMATED BASE WEIGHT

9'-8" GOOSENECK LENGTH - 106" SWING

25' DECK LENGTH / 102" WIDE

24" LOADED DECK HEIGHT

8" LOADED GROUND CLEARANCE

51" 5TH WHEEL HEIGHT

RAIL TRACK: HD STANDARD GAGE RAIL FULL LENGTH

DECK:

PERIMETER FRAME 16" CAMBERED DECK BEAMS

HD CROSSMEMBERS DESIGN FOR RAILROAD LOADING

22 D-RINGS TOTAL

24 FULL DEPTH FABRICATED OUTRIGGERS - POWDER COAT FINISH

2" APITONG OUTSIDE OF RAIL ONLY

20 DEGREE REAR DROP

REAR BOLSTERS FULL DEPTH WITH GROUSERS

LOCKAGE DECK TOOL BOXES

FLAG POCKETS FRONT OF DECK AND REAR OF TRAILER

SPECIAL 101" BOLT ON RAIL TRANSITION RAMPS - DECK TO SUBFRAME

RECESSED EXPANDED METAL BETWEEN RAILS

GOOSENECK:

MECHANICAL FOLDING GOOSENECK

PARALLEL LINK STYLE FOLDING GOOSENECK

TOOL WELL OVER KINGPIN

LINKAGE LOCK PINS LOCATED BOTH SIDES OF TRAILER

GOOSENECK LOAD ANGLE APPROX. 6 DEGREES

GOOSENECK RAMPS - FRONT PIN ON STEEL 6'-0" RAMPS

ADDITIONAL FEATURES:

RAIL CONFIGURATION INCLUDES SET OF RAMPS AND RAIL

REINFORCED FOR OPTIONAL 4TH FLIP AXLE

DOT RUBBER MOUNT DOT RUBBER MOUNTED SEALED BEAM LIGHTS WITH MODULAR HARNESS

PLUG AT REAR FOR ACCESSORY POWER

SHOT BLAST - PRIMED AND PAINTED BLACK POLYURETHANE



833-955-7732
www.loadkingmfg.com

LOAD KINGTM
BY CUSTOM TRUCK (1) SOURCE

*Load King reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.