

LOAD KING 403-4 DFPR RAIL TRAILER

DROP DECK HYDRAULIC FOLDING GOOSENECK



SPECS

SUBFRAME:

AIR RIDE SUSPENSION

THREE 25,000 LB AXLES

54 1/2 INCH AXLE SPACING SPRING BRAKES WITH ABS SYSTEM

TWELVE (12) 255/70 R 22.5 TIRES

HUB PILOTED BUDD TYPE DISC WHEELS

16 1/2 X 7 ABS BRAKING SYSTEM

OIL SEALS

REINFORCED FOR OPTIONAL 4TH FLIP AXLE

DIMENSIONS:

80,000 LB CAPACITY IN 8 FOOT LOAD CONCENTRATION @ 60 MPH

100,000/80,000 PSI YIELD STRENGTH STEEL CONSTRUCTION

21,300 LB ESTIMATED BASE UNIT WEIGHT

106 INCH AND 85 INCH SWING CLEARANCE

24 FOOT DECK LENGTH, 102 INCH DECK WIDTH

8 INCH LOADED GROUND CLEARANCE

DECK:

PERIMETER DESIGNED WITH FULL DEPTH 18 INCH BEAMS

CENTER LOADING DESIGNED CROSSMEMBERS IN GOOSENECK

14 D-RING RATED AT 10,000 LBS EACH

2 INCH APITONG FULL WIDTH

FLAG POCKETS FRONT OF DECK AND REAR OF TRAILER

24 DEGREE RADIUS REAR DROP

GOOSENECK:

PARALLEL LINK STYLE POWER FOLD GOOSENECK

LOW PROFILE SCRAPER STYLE

TOOL WELL OVER KINGPIN AREA FOR STORAGE

LINKAGE LOCK PINS ON BOTH SIDES OF TRAILER

7 DEGREE GOOSENECK LOAD ANGLE

GOOSENECK CONTROLS LOCATED AT DRIVERS SIDE OF GOOSENECK

13 HP SELF CONTAINED POWER PACK WITH COVER

ADDITIONAL FEATURES:

RAIL CONFIGURATION INCLUDES SET OF RAMPS AND RAIL

DOT RUBBER MOUNTED SEALED BEAM LIGHTS WITH MODULAR HARNESS

MUD FLAPS

SHOT BLAST - PRIMED AND PAINTED BLACK POLYURETHANE

DOUBLE REINFORCED TAILGATE



833-955-7732
www.loadkingmfg.com

LOAD KING
BY CUSTOM TRUCK (1) SOURCE

*Load King reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.