



LOAD KING 403 DFP FOLDING GOOSENECK TRAILER

DROP DECK HYDRAULIC FOLD



SPECS

DIMENSIONS:

80,000 LB CAPACITY IN 8 FOOT LOAD CONCENTRATION @ 60 MPH
100,000/80,000 PSI YIELD STRENGTH STEEL CONSTRUCTION
21,300 LB ESTIMATED BASE UNIT WEIGHT
106 INCH AND 85 INCH SWING CLEARANCE
24 FOOT DECK LENGTH, 102 INCH DECK WIDTH
8 INCH LOADED GROUND CLEARANCE

DECK:

PERIMETER DESIGNED WITH FULL DEPTH 18 INCH BEAMS
CENTER LOADING DESIGNED CROSSMEMBERS IN GOOSENECK
14 D-RING RATED AT 10,000 LBS EACH
2 INCH APITONG FULL WIDTH
FLAG POCKETS FRONT OF DECK AND REAR OF TRAILER
24 DEGREE RADIUS REAR DROP

SUBFRAME:

AIR RIDE SUSPENSION
THREE 25,000 LB AXLES
54 1/2 INCH AXLE SPACING SPRING BRAKES WITH ABS SYSTEM
TWELVE (12) 255/70 R 22.5 TIRES
HUB PILOTED BUDD TYPE DISC WHEELS
16 1/2 X 7 ABS BRAKING SYSTEM

OIL SEALS

GOOSENECK:

PARALLEL LINK STYLE POWER FOLD GOOSENECK
LOW PROFILE SCRAPER STYLE
TOOL WELL OVER KINGPIN AREA FOR STORAGE
LINKAGE LOCK PINS ON BOTH SIDES OF TRAILER
7 DEGREE GOOSENECK LOAD ANGLE
GOOSENECK CONTROLS LOCATED AT DRIVERS SIDE OF GOOSENECK
13 HP SELF CONTAINED POWER PACK WITH COVER

ADDITIONAL FEATURES:

DOT RUBBER MOUNTED SEALED BEAM LIGHTS WITH MODULAR HARNESS
MUD FLAPS
SHOT BLAST - PRIMED AND PAINTED BLACK POLYURETHANE
DOUBLE REINFORCED TAILGATE



833-955-7732
www.loadkingmfg.com

LOAD KING
BY CUSTOM TRUCK (1) SOURCE

*Load King reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.