



LOAD KING 453-4 DFP FOLDING GOOSENECK TRAILER

DROP DECK HYDRAULIC FOLD



SPECS

DIMENSIONS:

45 TONS IN 12' LOAD CONCENTRATION
100,000/80,000 PSI YIELD STRENGTH STEEL
22,900# ESTIMATED BASE WEIGHT
9'-8" GOOSENECK LENGTH - 106" SWING
25' DECK LENGTH
13 HP HONDA IGX MOTOR -
W/ EXTERNAL CONNECTIONS
102" WIDE

24" LOADED DECK HEIGHT
8" LOADED GROUND CLEARANCE
51" 5TH WHEEL HEIGHT

RAIL TRACK: HD STANDARD GAGE RAIL FULL LENGTH

ADDITIONAL FEATURES:

GROTE MICRO-NOVA DUAL INTENSITY LED LIGHTS
PLUG AT REAR FOR ACCESSORY POWER
SHOT BLAST - PRIMED AND PAINTED WHITE POLYURETHANE

DECK:

PERIMETER FRAME 16" CAMBERED DECK BEAMS
HD CROSSMEMBERS DESIGN FOR RAILROAD LOADING
22 D-RINGS TOTAL
24 FULL DEPTH FABRICATED OUTRIGGERS
2" APITONG OUTSIDE OF RAIL ONLY
20 DEGREE REAR DROP
REAR BOLSTERS FULL DEPTH WITH GROUSERS
LOCKAGE DECK TOOL BOXES
FLAG POCKETS FRONT OF DECK AND REAR OF TRAILER
SPECIAL 101" BOLT ON RAIL TRANSITION RAMPS
RECESSED EXPANDED METAL BETWEEN RAILS

OPTIONAL EQUIPMENT:

20,000 LB. HYD. WINCH MOUNTED IN SUB-FRAME
CENTER FILL-IN FOR FULL WIDTH WHEEL COVERS

SUBFRAME:

THREE (3) FIXED 27,500 LB AXLES
AIR RIDE SUSPENSION WITH AUTO & HEIGHT CONTROL
54" AXLE SPACING
TWELVE (12) 235/75R17.5 RADIAL TIRES
HUB PILOTED STEEL DISC WHEELS
OUTBOARD MOUNTED BRAKE DRUM WITH ABS
12 1/4" X 7 1/2" SPRING BRAKES WITH REMOTE DRAINS
COVERED WHEELS WITH GROUSER BARS
CENTER SUBFRAME COVERED
REINFORCED FOR OPTIONAL 4TH FLIP AXLE

GOOSENECK:

MECHANICAL FOLDING GOOSENECK
PARALLEL LINK STYLE FOLDING GOOSENECK
TOOL WELL OVER KINGPIN
LINKAGE LOCK PINS LOCATED BOTH SIDES OF TRAILER
GOOSENECK LOAD ANGLE APPROX. 6 DEGREES
GOOSENECK RAMPS - FRONT PIN ON STEEL 6'-0" RAMPS



833-955-7732
www.loadkingmfg.com

LOAD KING
BY CUSTOM TRUCK (1) SOURCE

*Load King reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.