

LOAD KING 503-554-SS-SF SIGNATURE SERIES TRAILER

55-TON HYDRAULIC DETACHABLE GOOSENECK WITH STINGER BAR & FLIP AXLE CAPABILITIES



SPECS

THREE 27,500 LB AXLES
54 ½ INCH AXLE SPACING
TWELVE 255/70R22.5 TIRES
TWELVE 8.25 X 22.5 HUB PILOTED, BUDD TYPE DISC WHEELS

REINFORCED FOR OPTIONAL SPREADER BAR & 4TH AXLE -

CONNECTIONS & AIR & ELECTRIC

STANDARD 3 TAIL LIGHT PACKAGE

WIDE LOAD SIGN POCKETS (NO SIGN)

EXCAVATOR CUTOUT BOTTOM, PLATED FIRST FOUR FEET, OPEN TO TAILGATE

50 TON THREE AXLE CAPACITY W/ STINGER/FLIP IN -

51 INCH 5TH WHEEL HEIGHT
GOOSENECK:
NON-GROUND BEARING GOOSENECK DESIGN
WET KIT OPERATION, LESS TRACTOR PORTION
HYDRAULIC SELF-LIFTING DETACHABLE GOOSENECK -

HYDRAULIC FRAME LIFT SUPPORT

AIR-ACTIVATED, SELF-LOCKING PIN ON GOOSENECK, POSITIVE LOCK

GOOSENECK CONTROLS LOCATED AT REAR OF GOOSENECK, FOR EASY ACCESS

RATCHET SYSTEM ENABLES MULTIPLE DECK HEIGHT SETTINGS

4 FULL DEPTH 16" CAMBERED DECK BEAMS

HEAVY DUTY I-BEAM CROSSMEMBERS ON ON 24" CENTER

6 D-RING PER SIDE OF DECK

FULL DEPTH SWING OUT OUTRIGGERS PER SIDE FOR 2" BOARDS

MID-TURN SIGNAL & CLEARANCE LIGHT GROTE MICRO-NOVA DUAL INTENSITY LED LIGHTS MUD FLAPS

RED & WHITE CONSPICUITY STRIPING
SHOT BLAST - PRIMED & PAINTED WHITE POLYURETHANE

SPREADER BAR: SB141

FLIP AXLE: FL201SF







833-955-7732 www.loadkingmfg.com



^{*}Load King reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.