



LOAD KING 503-856-DD-MB DETACHABLE GOOSENECK TRAILER

DROP DECK, USED WITH A MECHANICAL BOOSTER



SPECS

DIMENSIONS:

50 TONS IN 12' LOAD CONCENTRATION WITH 3 AXLES @ 60 MPH
 85 TONS IN 12' LOAD BASE WITH HELPER DOLLY AND 6 AXLES @ 60 MPH
 100,000/80,000 PSI YIELD STRENGTH STEEL
 45,800LB ESTIMATED BASE WEIGHT
 22'-10" GOOSENECK LENGTH INCLUDING 84" FLIP OVER EXTENSION
 211" SWING CLEARANCE WITH 127" & 103" SWING ON BASE GOOSENECK
 26' DECK LENGTH
 9 FT WIDE (108")
 26" LOADED DECK HEIGHT
 8" LOADED GROUND CLEARANCE
 51" 5TH WHEEL HEIGHT
 DECK:
 4 FULL DEPTH 18" CAMBERED DECK BEAMS
 36" FRONT FLIP RAMPS
 HEAVY DUTY I-BEAM CROSSMEMBERS ON 24" CENTERS
 6 D-RINGS PER SIDE
 7 LASHING BARS PER SIDE LOCATED INSIDE LIGHTENING HOLES
 26 FULL DEPTH FABRICATED OUTRIGGERS-POWDER COAT FINISH
 2 INCH APITONG OUTER WITH OPEN CENTER -
 AND 2" APITONG OUTRIGGER BOARDS
 30 DEGREE RADIUS REAR DROP
 ¾ HEIGHT REAR BOLSTER
 DECK TO SUBFRAME CONNECTION: REMOVABLE -
 WITH HORIZONTAL PIN
 SUBFRAME:
 THREE 30,000# AXLES
 INNER SUBFRAME SUSPENSION BEAMS AND CONNECTIONS
 FOR OPTIONAL 3 AXLE MECHANICAL BOOSTER
 30,000# AIR RIDE SUSPENSION WITH AUTO -
 AND ADJUSTABLE HEIGHT CONTROLS
 54-1/2" AXLE SPACING
 TWELVE 275/70R22.5 16 PR RADIALS
 HUB PILOTED STEEL DISC WHEEL
 OUTBOARD MOUNTED DRUMS
 16-1/2" X 7" BRAKES
 SPRING BRAKES ON 1 AXLE
 EXCAVATOR CUTOUT-OPEN TO TAILGATE
 WHEEL BOXES BETWEEN AXLES AND PLATFORM REAR AXLE 3
 GOOSENECK:
 HYDRAULIC NON-GROUND BEARING GOOSENECK DESIGN
 RATCHET SYSTEM ENABLES MULTIPLE RIDE HEIGHTS
 HYDRAULIC FRAME LIFT SUPPORT
 HYDRAULIC PRESSURE TO KINGPIN LOAD CHART
 AIR ACTIVATED SELF LOCKING PIN DESIGN-POSITIVE LOCK DESIGN
 GOOSENECK CONTROLS LOCATED AT REAR OF NECK ON DRIVERS SIDE
 WET KIT OPERATION, LESS TRACTOR PORTION
 ADDITIONAL EQUIPMENT:
 DOT RUBBER MOUNTED SEALED BEAM LIGHTS -
 WITH MODULAR HARNESS
 LOAD KING MUD FLAPS
 SHOT BLAST - PRIMED AND PAINTED BLACK POLYURETHANE
 COMPATIBILITY:
 HELPER DOLLY: HD853G
 MB603



833-955-7732
www.loadkingmfg.com

LOAD KING
 BY CUSTOM TRUCK (1) SOURCE

*Load King reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.