



SPECS

GENERAL DESCRIPTION: 100,000 LB. FIXED-NECK LOWBOY TRAILER WITH BEAVERTAIL & RAMPS

LOAD CAPACITY: 100,000 LBS. AT 65 M.P.H. (G.V.W.R. 120,200 LBS.)

OVERALL LENGTH: 42'-3"

DECK LENGTH: 18'-0" (FROM GOOSENECK RISER TO 1ST WHEEL WELL)

DECK WIDTH: 8'-6"

DECK HEIGHT: 35" UNLOADED

FRAME CONSTRUCTION: PIERCED MAINBEAM CONSTRUCTION WITH ONE PIECE INTERLOCKING CROSSMEMBERS.

MAINBEAMS: W16" X 77 LBS. PER FT., GRADE 50 HI-TENSILE.

CROSSMEMBERS: W10" I-BEAM X 12 LBS PER FT., GRADE 50 HI-TENSILE ON 30" CENTERS.

SIDERAILS: C12" X 20.7 LBS. PER FT. GRADE 50 HI-TENSILE.

DECKING: 2" NOMINAL OAK SECURED TO CROSS-MEMBERS WITH 5/16" TORQUE SCREWS.

LANDING GEAR: 4 POSITION, TUBULAR PIN DROP LEGS WITH SAND SHOES

SUSPENSION: HUTCH 9700 MULTI-POINT SPRING WITH RADIUS ROD AXLE TRACKING ADJUSTMENT,

AXLES: (3) DEXTER 25,000 LB. CAPACITY WITH OIL BATH HUBS.

BRAKES: 16-1/2" X 7" AIR WITH "WABCO" ANTI-LOCK BRAKING SYSTEM AND SPRING PARKING BRAKES.

WHEELS: 8 HOLE, HUB PILOTED DISC

TIRES: (12) 235/70R17.5, (H)

RAMPS: 60" X 22" SPRING ASSISTED.

HITCH: 2" SAE KING PIN.

TIE DOWNS: (8) HEAVY DUTY D-RINGS, 4 PER SIDE.

LIGHTS: 12 VOLT DOT & ICC APPROVED. ALL LIGHTS ARE LED TYPE AND FLUSH

MOUNTED IN RUBBER GROMMETS. WIRING IS RUN IN FLEXIBLE NEOPRENE JACKET AND MODULAR IN DESIGN. 7 WAY PLUG.



833-955-7732
www.loadkingmfg.com

LOAD KING
BY **CUSTOM TRUCK (1) SOURCE**

*Load King reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.