



SPECS

EQUIPMENT:

HI-RANGER LT40 INSULATED TELESCOPIC AERIAL DEVICE WORKING HEIGHT : 45.6'

BOTTOM OF PLATFORM HEIGHT: 40.6'

HORIZONTAL REACH: 26.6'

LOWER BOOM ARTICULATION: 0° TO 78°

UPPER BOOM ARTICULATION: -14° TO 80°

END-MOUNTED 24"X24"X42" PLATFORM RATED TO 350 LBS VINYL PLATFORM AND CONTROL COVER

BUCKET LINER

AUXILIARY LET DOWN

"CONTROL-PLUS" ONE HAND CONTROL

SAFETY HARNESS WITH ATTACHED LANYARD

UPPER BOOM REST TIE DOWN

HYDRAULIC PLATFORM TILT AT LOWER CONTROL

FULL PRESSURE, OPEN CENTER HYDRAULIC SYSTEM CONTINUOUS UNRESTRICTED WORM GEAR ROTATION

20 GALLON HYDRAULIC RESERVOIR

HYDRAULIC PLATFORM LEVELING

DUAL HYDRAULIC TOOL OUTLETS AT PLATFORM

"H" STYLE OUTRIGGERS

STANDARD CONFIGURATION:

7'6" CHIP BOX WITH HOIST ASSEMBLY

11"W X 18"H X 96"D PLATFORM POLE SAW BOX

24"W X 20"H X 18"D VENTED UNDERBODY TOOL BOX 36"W X 47"H X 15"D CABINET BOX WITH ROPE HOOKS REAR BUMPER WITH COMBO HITCH

SPRING MOUNTED CAB GUARD WITH ACCESS LADDER (2) WHEEL CHOCKS WITH UNDERBODY STORAGE

(2) OUTRIGGER PADS WITH UNDERBODY STORAGE ELECTRONIC TRAILER BRAKE CONTROLLER

HYDRAULIC TOOL OUTLET AT PLATFORM

CHASSIS SPECS:

RAM 5500 ST CHASSIS

6.7 LITER I-6 CUMMINS TURBO DIESEL ENGINE, 305 HP SCR TECHNOLOGY WITH DEF TANK

52 GALLON REAR FUEL TANK

84" CAB TO AXLE

6 SPEED AUTOMATIC TRANSMISSION

ANTI LOCK 4 WHEEL DISC BRAKES

7,000 LB FRONT AXLE

13,500 LB REAR AXLE WITH ANTI-SPIN DIFFERENTIAL FACTORY DE-RATED TO 19,500 LB GVWR

225/70RX19.5G TIRES FRONT (2) AND REAR (4)

50-STATE EMISSIONS COMPLIANT, CA. CLEAN IDLE AM/FM/CD/MP3 RADIO

AIR CONDITIONING

ENGINE BLOCK HEATER



888-925-0858

www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

