

MANTIS GTC-1200 130-TON CRAWLER CRANE

TELESCOPIC REACH TO 155'



SPECS

CRANE CAPACITY: 130-TONS AT 10'
BOOM: 5-SECTION, 42'1" - 155' / 360 DEGREE ROTATION
RETRACTED BOOM LENGTH: 42'1"
EXTENDED LENGTH: 155'
EXTENSION TIME: 170 SECONDS
ELEVATION ANGLES: -2 TO 82 DEGREE
ELEVATING TIME: 170 SECONDS
AUXILIARY BOOM HEAD
MAX. COUNTERWEIGHT: UPPER: 70,000 LBS., CARBODY: 20,000 LBS.
TRAVEL SPEED: .5MPH - 1.6 MPH / GRADABILITY: 52%
PLANETARY GEARED 2-SPEED WINCH
INCLUDES HYDRAULIC MOTOR, MULTI-DISC INTERNAL BRAKE AND
COUNTERBALANCE VALVE, DRUM ROTATION INDICATOR
EACH SIDE FRAME CONTAINS PILOT CONTROLLED, 2-SPEED TRACK DRIVE
ALL STEEL, WELDED STRUCTURE FRAME
MACHINE DATA LOGGING AND MONITORING SYSTEM
W/ HELLO-NET VIA INTERNET

ENGINE: CUMMINS QSL9 6-CYLINDER WATER COOLED 4 CYCLE,
TURBOCHARGED, AFTERCOOLED W/ 350HP@2100RPM, CLOSED
LOOP HYDROSTATIC TRANSMISSION

FULLY ENCLOSED AIR CONDITIONED ALL-STEEL MODULAR CAB
W/ LOCKABLE SLIDING DOOR, 20 DEGREE CAB TILT, REAR VIEW CAMERAS,
VENTED WINDOW, GRAB BARS, DEFROSTER, HEATER,
CIRCULATING FAN, 6-WAY ADJUSTABLE SEAT, JOYSTICK
CONTROL SWING W/ PREMIUM INSTRUMENTATION
SWING-CLOSED LOOP HYDROSTATIC TRANSMISSION W/ ELECTRONIC
DISPLACEMENT CONTROLLED BY PISTON PUMP



888-925-0858
www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

