



NATIONAL CRANE NBT36-127 TRACKED BUCKET TO 127' ON CTRAC8000 CRAWLER CARRIER



SPECS

NATIONAL CRANE NBT36-127
5-SECTION FULL POWER BOOM TO 127'
OPTIONAL BOOM LENGTH OF 103'

LONGEST IN ITS SIZE RANGE
MORE LIFTS W/OUT USE OF JIB

36 US TON CAPACITY RATING
135' MAX. TIP HEIGHT (MAIN BOOM)
190' MAX. TIP HEIGHT (W/ JIB)

55' TWO-PIECE JIB
LMI W/ GRAPHICAL DISPLAY

WORK AREA DEFINITION SYSTEM
NO TAIL SWING COUNTERWEIGHT

OPTIONAL TWO-MAN PLATFORM (YOKE STYLE)

COMPONENTS PAINTED PRIOR TO ASSEMBLY

SELF-LUBRICATING EASY GLIDE WEAR PADS

DELUXE OPERATOR'S CAB CONSTRUCTED OF

RIGID GALVANNEALED STEEL, TINTED SAFETY GLASS,

WELL INSULATED, MULTI-POSITION SEAT W/ ARM REST

MOUNTED SINGLE AXIS CONTROLS, VENTILATION FANS,

DIESEL HEATER, DUAL CAB MOUNTED WORKLIGHTS

24.7' OUTRIGGER SPAN W/GROUND LEVEL & IN-CAB OUTRIGGER CONTROLS

STRONGER STANDARD TORSION BOX

SPEEDY-REEVE BOOM TIP& SHEAVE BLOCKS

4-FUNCTION RADIO REMOTE CONTROLS

BEARINGS ON BOOM & RETRACT CABLES CAN BE GREASED THROUGH ACCESS

HOLES IN BOOM SIDE PLATES

STATE-OF-THE-ART CONTROL VALVE PROVIDES SMOOTHER OPERATION &

ELIMINATES PARTS, REDUCING REPAIR COSTS AND IMPROVING SERVICEABILITY

BOOM SECTIONS SUPPORTED BY ONE HYDRAULIC EXTEND CYLINDER FOR MINIMAL MAINTENANCE

2-SPEED GROOVED DRUM HOIST W/ CABLE PACKER, ELECTRONIC DRUM

ROTATION INDICATOR, LAST LAYER INDICATOR, 3RD WRAP INDICATOR

CTRAC8000:

VERSATILE, HIGH PAYLOAD, LOW GROUND PRESSURE TRACK VEHICLE

SPECIALLY DESIGNED TO DELIVER TODAY'S GENERATION OF HIGH CAPACITY CRANES & LONG-REACHING PLATFORMS TO THOSE JOBSITES YOU CAN'T
REACH ON RUBBER TIRES.

ITS UNIVERSAL CHASSIS DESIGN MAKES FOR EASY MOUNTING AND DISMOUNTING BETWEEN EQUIPMENT.

THE CRANE OR LIFT MOUNTED TO THE CTRAC8000 WILL SEE NO CHANGE IN THE STANDARD LIFT CAPACITIES, CHARTS OR RANGE DIAGRAMS

THERE ARE NO MODIFICATIONS TO THE OUTRIGGERS OR CRITICAL COMPONENTS, MAINTAINING THE MANUFACTURER'S WARRANTY

STANDARD TIER 4 CUMMINS ENGINE IS COMPLIANT WITH ALL US EMISSIONS STANDARDS

EXPORT ENGINES AVAILABLE

DUAL BOGIE WHEELS MAXIMIZE STABILITY, MAINTAIN EVEN GROUND PRESSURE & IMPROVE LATERAL STABILITY

ACCEPTS ANY CRANE/AERIAL DEVICE/TRUCK-MOUNTED EQUIPMENT REQUIRING AN 80K GVWR CHASSIS



888-925-0858

www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

