



RING-O-MATIC 550-VACEX VACUUM EXCAVATOR

550 HI CFM CONFIGURATION



SPECS

POWERED BY CAT-UNMATCHED
PERFORMANCE AND RELIABILITY
VACUUM PUMP BLOWERS BY GARDNER DENVER-
RUGGED & HIGH PERFORMANCE
PREMIUM SILENCER PACKAGE -
REDUCED NOISE INTERFERENCE
RUGGED CONSTRUCTION THE WAY A CONTRACTOR
NEEDS IT - HEAVY DUTY FRAMES & LARGEST AXLE
CAPACITY IN ITS CLASS
COMPACT LOW PROFILE FOR PREMIUM OPERATOR
VISIBILITY & STABILITY ACROSS RUGGED TERRAIN
CONSTRUCTED FOR VIGOROUS APPLICATION
BALANCED DESIGN WITH
OPTIMAL TONGUE WEIGHT
LEADS THE INDUSTRY IN EQUIPMENT WIDTH
FOR SUPERIOR VERSATILITY AND DRIVABILITY
REVERSE FLOW - STANDARD
RAPID REMOVAL OF TANK CONTENTS
EXCLUSIVE SINGLE HANDLE DOOR LATCH
LEADS THE INDUSTRY IN FEASIBILITY,
ALLOWING (1) OPERATOR TO DRILL 3' DEEP HOLES
IN LESS THAN 30 SECONDS
DIMENSIONS: 85" H X 19.5' L
GVWR: 13,100#
ST235/80 R16 LOAD RANGE TIRES
TORSION SUSPENSION
OPERATOR CONTROLS - FRONT CURBSIDE
W/ LOCKABLE CABINET
550 HI CFM CONFIGURATION
TANDEM AXLE TRAILER MOUNT -
TRUCK & SKID MOUNTING AVAILABLE
SPOILS CAPACITY: 550 GALLONS / 2.7 CU. YDS.
50 HP CAT INDUSTRIAL WATER-COOLED
DIESEL; TIER 4I
FUEL CONSUMPTION: 3.14 GPH
FUEL TANK CAPACITY: 29 GALLONS
VACUUM PUMP/BLOWER
DISPLACEMENT: 1000 CFM
TONGUE WEIGHT: <1200 LBS. (EASIER ON TRUCKS)
HEAVY-DUTY FRAME & AXLES: 6" HD FRAME
W/ 12,000LBS. AXLE CAPACITY
LOAD LEVEL INDICATOR & AUTO SHUT-OFF: SIGHT GLASS
WATER PUMP SYSTEM:
WATER TANK CAPACITY: 2 X 100 GALLONS
WATER PRESSURE: 4,000 PSI
WATER SUPPLY: 6 GPM
WATER SUPPLY HOSE: 50' X 3/8"
WATER SUPPLY REEL: REAR CURBSIDE
WATER PUMP DRIVE: BELT W/ ELECTRIC CLUTCH



888-925-0858
www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

