



SPECS

INTEGRATED REEL CARRIER

5-GROOVE BULLWHEELS WITH PRECISION SOLD-CAST URETHANE LININGS
FULLY ADJUSTABLE & ARTICULATED DISC CALIPER BRAKING OF BULLWHEELS
QUICK RELEASE OF BULLWHEEL BRAKE SYSTEMS FOR EASY REEL CHANGE

TENSIONING CAPACITY, MAX: 3,000 LB

LINE SPEED, MAX: 4 MPH

BULLWHEEL SIZE: 36 IN. DIA.

BULLWHEEL GROOVE COUNT: 5 PER BULLWHEEL

GROOVE RADIUS: 3/4 IN.

GROOVE LINING MATERIAL: POLYURETHANE, 3/4 IN. THICKNESS

TENSIONING BRAKE: 20 IN. DIA. DISC, BRONZE

BRAKE CONTROL: 3-AXIS CALIPER, MANUAL

MAX REEL SIZE: 84 IN. OD X 52 IN. WIDE

MAX REEL WEIGHT: 8,000 LB., FULLY LOADED

REEL SHIFT DIAMETER: 2-5/8 IN.

REEL BRAKE: 16 INCH. DIA DISC, BRONZE

OPERATOR'S SAFETY SCREEN & SEAT: STANDARD

LENGTH, OVERALL, NOM: 19 FT.

WIDTH, OVERALL, NOM: 8 FT., 6 IN.

HEIGHT, OVERALL, NOM: 9 FT.

SUSPENSION: LEAF SPRING

AXLE CONFIGURATION: SINGLE

BRAKES, TRAILER: ELECTRIC, WITH SAFETY BREAK-AWAY SWITCH



888-925-0858

www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

