

SHERMAN + REILLY DDHX-75-T UNDERGROUND PULLER

HYDRAULIC DUCT DAWG WITH 7,500 LBS. MAX. PULLING CAPACITY



SPECS

PULLING CAPACITY MAX: 7,500 LB

BULLWHEELS: TWIN CAPSTAN, 6 IN. DIA., 5-GROOVE FOLLOWED BY 6-GROOVE

GEARBOX & LINE SPEED

1ST GEAR 0-60 FPM @ 7,500 LB WITH DEMAND PAYOUT

2ND GEAR 0-120 FPM @ 3,500 LB WITH DEMAND PAYOUT

3RD: 0-285 FPM @ 1,500 LB WITH DEMAND PAYOUT

DRIVE SYSTEM: HYDRAULIC

HYDRAULIC FLUID: ISO GRADE 32

HYDRAULIC RESERVOIR: 25 GALLONS WITH COLD WEATHER PACKAGE OPTIONAL

ENGINE: 42 HP, DIESEL, WATER-COOLED, ELECTRIC START

FUEL CAPACITY: 13 GALLONS

PULLING ROPE: 3/8 IN., 6 X 25 XIP IWRC STEEL WIRE ROPE, 2,000 FT

BOOM: HYDRAULIC, JOYSTICK CONTROLLED, 3-AXIS, >50 DEGREE SWING ARC - 17 IN. SHEAVE W/ 60 DEGREE SWIVEL HEAD

LEVELWIND: DUAL AUTOMATIC FAIRLEAD SHEAVES

PULLER MOUNTED CONTROLS: HYDRAULIC OVERRIDES; JACKS, BOOM

PULLER WIRELESS CONTROLS: CANBUS CONTROLLER COMMUNICATING W/ RADIO CONTROLLED REMOTE, 300 FT. MA

FOOTAGE COUNTER: ELECTRONIC, ACTUAL FOOTAGE, PAY-IN AND PAY-OUT WITH MEMORY

HYDRAULIC TOOL CIRCUIT: OPTIONAL - 7 GPM @ 2,500 PSI AUXILIARY

PULLING CONNECTORS: ROTATION-RESISTANT: (1) RATED AT 3,000 LB & (1) RATED AT 8,800 LB

FRAME CONSTRUCTION: STEEL TUBING, CONTINUOUS-WELD

LENGTH, OVERALL, NOMINAL: 186 IN.

WIDTH, OVERALL, NOMINAL: 95 IN.

HEIGHT, OVERALL, NOMINAL: 114 IN.

WEIGHT: NOMINAL 5,000 LB W/OUT ROPE - 7,200 LB WITH ROPE

GVWR: 8,800 LB

SUSPENSION: LEAF SPRING

AXLE CONFIGURATION: SINGLE

WHEEL CONFIGURATION & TIRES : SINGLE, LT235/75R17.5

BRAKES, TRAILER: ELECTRIC, WITH SAFETY BREAK-AWAY SWITCH

TOWING ATTACHMENT: 3 IN. ADJUSTABLE PINTLE EYE

SAFETY CHAINS: 2 EA., WITH HOOKS

TIE-DOWNS: 5/8 IN. DIAMETER STEEL D-RINGS

FRONT / NOSE JACK: HYDRAULIC, WITH SHOE - 144 IN. SQUARE OF SURFACE AREA

STABILIZING JACKS: HYDRAULIC, WITH SHOE AT REAR COMERS - 144 IN. SQUARE OF SURFACE AREA

ELECTRICAL SYSTEM : 12 VDC, 60 AMP ALTERNATOR

LIGHTS, NAVIGATION: US DOT LED, 12 VDC

BATTERY: 12 V

GROUNDING: 3/4 IN. DIA. COPPER-CLAD STEEL GROUND LOOPS (4)

 ${\sf FIRE}\;{\sf EXTINGUISHER}:{\sf ABC}$

COLOR: WHITE







888-925-0858 www.customtruck.com



^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.