



SHERMAN + REILLY P-2000X SINGLE DRUM PULLER

WITH 20,000 lb. PULLING CAPACITY



SPECS

FULLY HYDRAULIC/DIRECT DRIVE SYSTEM
 175 HP INDUSTRIAL DIESEL ENGINE
 (4) HYDRAULIC JACKS FOR LEVELING
 CENTRALIZED ENGINE CONTROLS - CAN-BUS TECHNOLOGY
 4 MPH AVG LINE PULLING SPEED
 DIGITAL CONTROLS W/ REAL TIME MONITORING
 22,000' 20MM ANTI-TWIST BRAIDED WIRE ROPE
 .92 LBS./ FT. - 58,900 LBS. MIN BREAK STRENGTH
 ELECTRICALLY ACTUATED, AUTO CONTROLLED LEVELWIND
 SAFE-ZONE CAB, FULLY ENCLOSED/ SINGLE DOOR
 TRI-AXLE CONFIGURATION
 ADJUSTABLE PINTLE EYE, W/ (2) SAFETY CHAINS & HOOKS
 (4) STEEL D-RING TIE DOWNS
 (2) 12V, 720 CCA BATTERIES
 DOT-APPROVED 12V LED LIGHTS
 (4) 3/4" DIA COPPER-CLAD STEEL GROUNDING LOOPS
 ELECTRIC BRAKE TRAILER
 DIMENSIONS:
 23' 8" OVERALL LENGTH
 8' 6" WIDTH
 10' 10" HEIGHT
 45,000 LBS. W/ ROPE
 50,000 LBS. GVWR
 HARDLINE REEL: 30" DIAM CORE, 76" OUTSIDE WIDTH, 50"
 INSIDE WIDTH
 76" FLANGE DIAMETER



888-925-0858
www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

