



# SHERMAN + REILLY P-1400X SINGLE DRUM PULLER

WITH 15,250 LB. PULLING CAPACITY



# SPECS

FULLY HYDRAULIC/ DIRECT DRIVE SYSTEM  
LATERAL ARTICULATING DRUM ENGAGEMENT  
SAFE-ZONE CAB, FULLY ENCLOSED/ SINGLE DOOR  
HORIZONTAL FLOATING AUTOMATIC LEVELWIND  
(3) HYDRAULIC JACKS  
15,250 LBS. MAX PULLING CAPACITY, 14,000 LBS. TOD  
4 MPH AVERAGE LINE SPEED, 10 MPH PAYOUT  
DIGITAL CONTROLS W/ REAL-TIME TENSION MONITORING  
DIRECT HYDRAULIC DRIVE SYSTEM  
173 HP TIER 3 DIESEL ENGINE, WATER COOLED  
HYDRAULICALLY DRIVEN, AUTOMATICALLY CONTROLLED LEVELWIND  
TRAILER W/ ANTI-LOCK AIR BRAKES  
3" PINTLE EYE W/ SAFETY CHAINS/ HOOKS  
HYDRAULIC REAR & NOSE JACKS  
DRUM DIMENSIONS:  
54" DRUM W/ OPT. 15,000' (MAX) UNITREX SYNTHETIC ROPE  
30" CORE DIAMETER  
76" TOTAL OUTSIDE WIDTH  
64" INSIDE WIDTH  
54" FLANGE DIAMETER  
UNIT DIMENSIONS:  
21' 8" OVERALL LENGTH  
8' 6" OVERALL WIDTH  
10' 10" OVERALL HEIGHT  
18,500 LBS. WEIGHT  
30,000 LBS. GVWR



888-925-0858  
[www.customtruck.com](http://www.customtruck.com)

\*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

