



# SHERMAN + REILLY T-2608 PULLER-TENSIONER

WITH 8,000 LB. TENSIONING CAPACITY PER BULLWHEEL





# SPECS

## SPECIFICATIONS:

- TENSIONS (2) CONDUCTORS AT ONCE
- 8,000 LB. MAX TENSIONING CAPACITY, PER BULLWHEEL
- SYNCHRONIZED TENSIONING, UP TO (3) MACHINES
- PROTECTED, OFF-GROUND OPERATOR POSITION
- (2) SETS HYDRAULICALLY-DRIVEN BULLWHEELS FOR 4 TOTAL BULLWHEELS
- FULLY ENCLOSED SAFE-ZONE CAB W/ HEATING & COOLING
- DIGITAL CONTROLS & SELF-DIAGNOSTICS
- 4 MPH MAX LINE SPEED
- HYDRAULIC, MOTOR-DRIVEN TENSIONING BRAKE
- SPRING-APPLIED FAIL-SAFE BRAKE
- AUTOMATIC BRAKE CONTROL, PER OPERATOR SETTING
- (4) ADJUSTABLE FAIRLEAD ROLLERS, (2) FRONT & REAR
- TANDEM AXLE CONFIGURATION TRAILER
- 3" ADJUSTABLE PINTLE EYE W/ SAFETY CHAINS/HOOKS
- (2) HYDRAULIC, ANTI-SLIDE FRONT/NOSE JACKS, W/ SHOES
- (2) HYDRAULIC, ANTI-SLIDE CORNER STABILITY JACKS, W/ SHOES
- 72HP WATER COOLED DIESEL ENGINE
- 12 GALLON FUEL CAPACITY
- 20 GALLON HYDRAULIC RESERVOIR
- DIMENSIONS:
- 60" DIAMETER BULLWHEELS
- (5) 1" RADIUS GROOVES PER BULLWHEEL
- 25' OVERALL LENGTH
- 8' 6" OVERALL WIDTH
- 10' 4" OVERALL HEIGHT
- 18,500 LBS.
- 24,000 LBS. GVWR



888-925-0858

[www.customtruck.com](http://www.customtruck.com)

\*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

