



SHERMAN + REILLY T7212 PULLER-TENSIONER

WITH 25,000 LB. TENSIONING CAPACITY



SPECS

STANDARD FEATURES:

12,000 LBS. TENSIONING CAPACITY, PER BULLWHEEL PAIR

4 MPH MAX LINE SPEED

(4) 72" DIAMETER BULLWHEELS, 5 GROOVES EACH

1 1/8" GROOVE RADIUS

MOTOR-DRIVEN HYDRAULIC TENSIONING BRAKE

AUTOMATIC BRAKE CONTROL SYSTEM

80HP DIESEL ENGINE, WATER COOLED

20 GALLON HYDRAULIC RESERVOIR

(2) FRONT, (2) REAR QUICK CONNECT EXTERNAL HYDRAULIC CONNECTIONS

(2) FRONT, (2) REAR ADJUSTABLE FAIRLEAD ROLLERS

FULLY ENCLOSED CAB W/ A/C & HEAT

GENERAL SPECIFICATIONS:

27' OVERALL LENGTH

8' 6" WIDTH

11' 10" TALL

30,000 LBS. GVWR

(2) FRONT, (2) REAR HYDRAULIC JACKS

US D.O.T. LIGHTING

CAB-TOP FLOOD LIGHTS

3/4" COPPER-CLAD STEEL GROUND LOOPS

WHEEL CHOCKS



888-925-0858

www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

