

TSE DP-3.5-4H 4 DRUM PULLER

WITH 3,000 lb. FULL DRUM PULLING CAPACITY



SPECS

DESCRIPTION

3,500 LB. FULL DRUM PULLING

CAPACITY. INFINITELY VARIABLE SPEED 0-4.0 MPH (FULL DRUM)

FOUR SEPARATE HEAVY DUTY PULLING
DRUMS WITH HYDRAULIC LEVELWINDS ALLOW
FOR SIMULTANEOUS OR INDIVIDUAL PULLING IN
OF THREE CONDUCTORS AND A GROUND WIRE.

EACH DRUM 60" DIA. X 31" ID WIDTH X 18" CORE. 15,000' OF 5/8" ROPE PER DRUM.

FREE-WHEELING DRUM DISCONNECT FOR HIGH SPEED PAYOUT, 24" BRONZE OVERSPIN BRAKES ON EACH DRUM, MECHANICAL DRUM LOCKING PINS AND POSITIVE MANUAL LEAVER LOCK ON REEL SPOKES.

CLOSED LOOP HYDROSTATIC HYDRAULIC
PLANETARY CHAIN DRIVE, SPRING APPLIED HYDRAULIC
PRESSURE RELEASED HOLDING BRAKE.

30 GALLON HYDRAULIC TANK WITH LEVEL AND TEMP GAUGE. HYDRAULIC FRONT TONGUE JACK AND TWO MANUAL REAR JACKS OPERATOR CONTROLS.

BOLTED FOLD DOWN SAFETY SCREEN
DIRECTION CONTROL LEAVER WITH INFINITE SPEED
ADJUSTMENT AND ANTI-PAYOUT STOP.

ADJUSTABLE PULL / TENSION CONTROL WITH BYPASS IF

PRESET PRESSURE IS REACHED.

HOLDING BRAKE APPLY / RELEASE CONTROL

HYDRAULIC SYSTEM PRESSURE GAUGE AND FILTER GAUGES.

LEVELWIND SPEED AND DIRECTION CONTROL

ENGINE

JOHN DEERE 4045T 87 HP 4-CYLINDER DIESEL, BLOCK HEATER LIQUID COOLED, GLOW PLUGS, HOUR METER, MANUAL THROTTLE

DIMENSIONS:

258" LONG, 96" WIDE, 108" TALL (SCREEN DOWN) 26,000 LBS. W/ ROPE







888-925-0858 www.customtruck.com



^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.