

## TSE T30/36-BWRC BULLWHEEL TENSIONER WITH REEL CARRIER & 7,000 LB. REEL CAPACITY



## **SPECS**

## FEATURES:

36" BULLWHEEL, (4) 1-1/4" GROOVES W/ REPLACEABLE LINING SEGMENTS

UP TO 3,000 LBS. CONTROLLED, CONTINUOUS CONDUCTOR TENSION

0 - 4 MILES PER HOUR LINE SPEED

7,000 LBS. MAX REEL CAPACITY, 2-5/8" SHAFT DIAMETER, 54" WIDE, & 72" DIAMETER

HYDRAULIC DISC BRAKES, EQUAL TO EACH BULLWHEEL

OPEN REEVE BULLWHEELS ALLOW EASY CONDUCTOR INSTALL & REMOVE

STRAIGHT VERTICAL LIFT ON REEL SHAFT

TAIL FAIRLEAD W/ (3) ROLLERS

## TRAILER:

LEAF SPRING SUSPENSION ON TANDEM AXLES

ELECTRIC TRAILER BRAKE

(4) 8.75 X 16.5LT TIRES

3-INCH PINTLE EYE W/ (4) HEIGHT ADJUSTMENTS

(1) FRONT & (2) REAR MANUAL SCREW TYPE JACKS, W/ DROP LEGS

(4) TRAILER LIGHTS

UNIT DIMENSIONS:

17' LONG

8' WIDE

7.5' TALL

3,800 LBS.







888-925-0858 www.customtruck.com



<sup>\*</sup>Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.