



TSE T50/52-BWRC BULLWHEEL TENSIONER

WITH REEL CARRIER & 11,500 LB. REEL CAPACITY



SPECS

GENERAL SPECIFICATIONS:

MAX 5,000 LB. CONTINUOUS TENSION @ 4 MPH

52" BULLWHEEL DIAMETER

1.5" GROOVE DIAMETER

(5) GROOVES PER BULLWHEEL

96" MAX REEL DIAMETER

54" MAX REEL WIDTH (52" W/ HYDRAULIC REWIND)

12,500 MAX REEL WEIGHT

2-5/8" REEL SHAFT DIAMETER

STANDARD EQUIPMENT:

ANTI-SURGE ACCUMULATOR

TILTED BULLWHEELS

36" BRONZE DISC BRAKES

CENTRAL OPERATOR'S PANEL W/ TENSION CHART

QUICK CHANGE REEL SHAFT CHANGE SYSTEM

16" DIAMETER BRONZE REEL BRAKE

(3) ROLLER TAIL FAIRLEAD

TANDEM AXLE TRAILER W/ ELECTRIC BRAKES

FRONT & REAR DROP-LEG JACKS



888-925-0858

www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

