



# TEREX COMMANDER 4042 TRACKED DIGGER DERRICK

ON IHI IC-50 CRAWLER CARRIER WITH 42.5' SHEAVE HEIGHT



# SPECS

C4042 DIGGER DERRICK:  
UPPER CONTROLS –  
24" X 24" X 42" PLATFORM  
WITH INSULATED LINER  
TRANSFERABLE POLE CLAWS  
15,000 LB BOOM WINCH TIP  
11,250 LB CAP. @ 10' RADIUS  
COMMAND POST  
RADIAL OUTRIGGER MOUNTED  
ON BACK OF TRACK MACHINE  
12,000 LB TWO SPEED DIGGER  
WITH 18" ROCK RIPPER AUGER

IHI IC-50:  
ENGINE: ISUZU 4JJ1X / 121 HP  
TIER 3 STAGE 3A EMISSION  
7.5 MPH (UNLOADED)  
4.7 MPH (LOADED)  
HST TRANSMISSION SYSTEM WITH  
HST BRAKE + AUTO PARKING BRAKE  
18.7" GROUND CLEARANCE  
24" TRACK WIDTH  
OPEN CANOPY SINGLE CAB



888-925-0858  
[www.customtruck.com](http://www.customtruck.com)

\*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

