



# TEREX COMMANDER 6060 TRACKED DIGGER DERRICK

ON PRINOTH PANTHER T-12 CRAWLER CARRIER WITH 60' SHEAVE HEIGHT





# SPECS

## TEREX C6060:

UPPER CONTROLS - 24" X 24" X 42" PLATFORM WITH INSULATED LINER

TRANSFERABLE POLE CLAWS

15,000 LB TURRET MOUNTED WINCH

18,100 LB CAPACITY AT 10' RADIUS BARE BOOM COMMAND POST

RADIAL OUTRIGGERS MOUNTED ON TRACK MACHINE

12,000 LB TWO SPEED DIGGER

24", 30" & 36" ROCK RIPPER AUGERS AVAILABLE

SPRING LOADED HYDRAULIC HOSE REEL

30,000 LB HYDRAULIC WINCH MOUNTED ON THE FRONT OF TRACK MACHINE

NO WIDTH OR HEIGHT PERMIT REQUIRED

## PRINOTH T12:

CATERPILLAR C7.1 ACERT / 250 HP

TIER 4 EMISSION

6.2 MPH (UNLOADED)

HST TRANSMISSION SYSTEM WITH HST BRAKE + EMERGENCY BRAKE

21" GROUND CLEARANCE

29.6" TRACK WIDTH

ENCLOSED SINGLE CAB WITH AC/HEAT



888-925-0858  
[www.customtruck.com](http://www.customtruck.com)

\*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

