



# TEREX GENERAL 80 TRACKED DIGGER DERRICK

ON PRINOTH GO-TRACT GT-4500 CRAWLER CARRIER WITH 80.3' SHEAVE HEIGHT



# SPECS

TEREX GENERAL 80:

SHEAVE HEIGHT: 80'

MAXIMUM CAPACITY: 48,790 LBS.

4-STAGE HYDRAULICALLY EXTENDED STEEL BOOMS

TRANSFERABLE POLE CLAWS

15,000 LBS. TURRET MOUNTED WINCH

COMMAND POST CONTROL STATION

RADIAL OUTRIGGERS MOUNTED ON TRACK MACHINE

14,000 LB. 2-SPEED DIGGER WITH 24", 30" AND 36" ROCK RIPPER AUGERS AVAILABLE

SPRING-LOADED HYDRAULIC HOSE REEL

30,000 LB. HYDRAULIC WINCH MOUNTED ON THE FRONT OF THE TRACK MACHINE

PRINOTH GT-4500:

CATERPILLAR C9/280HP

TIER-3 EMISSIONS

6.3 PMH (UNLOADED)

HST TRANSMISSION SYSTEM WITH HST + EMERGENCY BRAKE

21" GROUND CLEARANCE / 43" TRACK WIDTH

ENCLOSED SINGLE CAB WITH A.C./HEAT

DIMENSIONS:

WEIGHT: 64,000 LBS.

LENGTH: 31'

OAW: 11'5"

HEIGHT: 12'



888-925-0858  
[www.customtruck.com](http://www.customtruck.com)

\*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

