

TEREX A330-12 PRESSURE DIGGER

AUGER DRILL WITH 12' DRILL DEPTH



SPECS

DRILL DEPTH: 12'

DRILL TORQUE: 52.588 FT-LBS.

MAST HEIGHT/LOWEST OVERALL WORKING

HEIGHT/POLE-SETTER RETRACTED: 25'10"

MAST HEIGHT-MAX. OVERALL WORKING HEIGHT/

POLE-SETTER EXTENDED: 31'10"

MAST LEVEL:

35 DEGREES RIGHT / 35 DEGREES LEFT

FRAME TRAVEL CLEARANCE:

4'3" EXTENDED / 1'3" RETRACTED

POLE GUIDES

240 DEGREE TURNTABLE BASE ROTATION ANGLE

36 IN. FRAME TRAVEL, FORE AND AFT

MULTI-FUNCTION JOYSTICK CONTROLS

50 GALLON FUEL CAPACITY

92 GALLON HYDRAULIC RESERVOIR

CAT C4.4 DIESEL ENGINE -

TIER 3 CERTIFIED

POWERSHIFT 3 SPEED TRANSMISSION

100 DEGREE SWING OUT

OPERATOR'S STATION

REAR HYDRAULIC A-FRAME OUTRIGGERS

OUTRIGGER MOTION ALARM

KELLY BAR, 3"

MAST SET-UP WITHOUT / WINCH LINE PAYOUT

OUTRIGGER INTERLOCK

HYDRAULIC TOOL CIRCUIT -

INCLUDES GROUND ACCESS SWITCH

AVAILABLE ON MANY DIFFERENT CHASSIS MAKES, MODELS







888-925-0858 www.customtruck.com



^{*}Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.