



TEREX A330-15 PRESSURE DIGGER

AUGER DRILL WITH 15' DRILL DEPTH



SPECS

DRILL DEPTH: 15'
MAST HEIGHT/LOWEST OVERALL WORKING HEIGHT/
POLE-SETTER RETRACTED: 28'10"
MAST HEIGHT-MAX. OVERALL WORKING HEIGHT/
POLE-SETTER EXTENDED: 34'10"
DRILL TORQUE: 52,588 FT-LBS.
MAST LEVEL:
35 DEGREES RIGHT
35 DEGREES LEFT
FRAME TRAVEL CLEARANCE:
4'3" EXTENDED
1'3" RETRACTED
POLE GUIDES
240 DEGREE TURNTABLE
BASE ROTATION ANGLE
36 IN. FRAME TRAVEL, FORE AND AFT
MULTI-FUNCTION JOYSTICK CONTROLS
50 GALLON FUEL CAPACITY
92 GALLON HYDRAULIC RESERVOIR
CAT C4.4 DIESEL ENGINE —
TIER 3 CERTIFIED
POWERSHIFT 3 SPEED TRANSMISSION
100 DEGREE SWING OUT
OPERATOR'S STATION
REAR HYDRAULIC A-FRAME OUTRIGGERS
OUTRIGGER MOTION ALARM
KELLY BAR, 3"
MAST SET-UP WITHOUT
WINCH LINE PAYOUT
OUTRIGGER INTERLOCK
HYDRAULIC TOOL CIRCUIT INCLUDES GROUND ACCESS SWITCH
AVAILABLE ON MANY DIFFERENT CHASSIS MAKES, MODELS



888-925-0858
www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

