



VERSALIFT VST-47-I BUCKET TRUCK

47' ARTICULATING TELESCOPIC MATERIAL HANDLING AERIAL DEVICE



SPECS

HORIZONTAL REACH: 30'9"

WORKING HEIGHT: 51'4"

PLATFORM: CLOSED FIBERGLASS 24" X 24" X 42"

MAX. PLATFORM CAPACITY: 500 LBS.

PLATFORM ROTATION: 180 DEGREES

OUTER/INNER BOOM ARTICULATION: -25 TO +85 DEGREES

LOWER BOOM: 0 TO 84 DEGREES

INNER BOOM EXTENSION: 103"

BOOM ROTATION: CONTINUOUS 360 DEGREES

MATERIAL HANDLING JIB CAPACITY: 1,000 LBS.

UPPER BOOM INSULATION GAP: 64"

LOWER BOOM INSULATION GAP: 12"

INDIVIDUAL FULL-PRESSURE LOWER CONTROLS
AT TURRET ACTUATE ALL BOOM FUNCTIONS

LOWER CONTROL STATION EQUIPPED W/ SELECTOR VALVE
TO OVERRIDE THE UPPER CONTROLS

SINGLE STICK UPPER CONTROL

HYDRAULIC PLATFORM LEVELING SYSTEM

OPEN CENTER HYDRAULICS

OUTRIGGER/BOOM INTERLOCK

17 GALLON HYDRAULIC OIL RESERVOIR INTEGRAL TO THE PEDESTAL

NON-LUBE BEARINGS USED AT MOST POINTS OF MOTION



888-925-0858

www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

