



VERSALIFT VST-50-TN BUCKET TRUCK

50' TOP-MOUNT ARTICULATING TELESCOPIC AERIAL DEVICE



SPECS

HEAVY DUTY, NON-INSULATED TOP MOUNT PLATFORM

UP TO 55'7" OF WORKING HEIGHT

30'7" OF HORIZONTAL REACH

JIB/WINCH CAPACITY: 200 LBS.

TOP MOUNTED PLATFORM W/ 500 LBS. CAPACITY

PLATFORM ROTATION: 180 DEGREES

0 TO +84 DEGREES LOWER BOOM ARTICULATION

0 TO +85 DEGREES UPPER BOOM ARTICULATION

360 DEGREES CONTINUOUS ROTATION

103" INNER BOOM EXTENSION

LOW MAINTENANCE NON-LUBE BEARINGS

OPTIONAL EMERGENCY POWER

SUPERIOR STABILITY W/ (2) SETS OF OUTRIGGERS

STOWS ON SHORT WHEELBASE, NON-CDL CHASSIS

FULL PRESSURE UPPER & LOWER CONTROLS

ENGINE START/STOP AT UPPER CONTROLS

OUTER & INNER BOOM ASSEMBLIES: STEEL CONSTRUCTION



888-925-0858

www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

