



VERSALIFT VST-7500-E108 BUCKET TRUCK

111' ARTICULATING TELESCOPIC ELEVATOR AERIAL DEVICE



SPECS

111'11" WORKING HEIGHT
46'10" HORIZONTAL REACH
800 LBS. MAX. PLATFORM CAPACITY (700 W/ JIB)
360 DEGREE CONTINUOUS ROTATION
OUTRIGGER BOOM INTERLOCK
PAINTED PRIOR TO ASSEMBLY
SINGLE STICK CONTROL
FULL PRESSURE HYDRAULICS
TRUGUARD(TM) DIELECTRIC ISOLATED CONTROLS
24" X 48" X 42" PLATFORM
LIGHTER UNIT FOR OFF-ROAD TRAVELING
STOWED TRAVEL HEIGHT: 12'6"
108" UPPER BOOM INSULATION GAP
24" LOWER BOOM INSULATION GAP
LOWER BOOM LIFT EYE CAPACITY (OPT.): 1500 LBS.
MAX. JIB CAPACITY (OPT.): 2000 LBS.
OPERATING PRESSURE: 3000 PSI
FLOW RATE: 10 GPM
FILTRATION: 10 MICRON RETURN / 100 MESH SUCTION
SYSTEM: OPEN CENTER
POWER SOURCE: PTO PUMP
WEIGHT OF LIFT & ELEVATOR: 18,300 LBS. (W/OUT SUBFRAME & OUTRIGGERS)



888-925-0858
www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

