



VERSALIFT VST-9000-I TRACKED BUCKET

90' ARTICULATING TELESCOPIC ELEVATOR AERIAL DEVICE
ON CTRAC8000 CRAWLER CARRIER



SPECS

MAX WORKING HEIGHT: 95'
MAX. HORIZONTAL REACH: 56'8"
LOWER BOOM LIFT EYE CAPACITY (OPT.): 1,500 LBS.
MAX. JIB CAPACITY (OPT.): 1,000 LBS.
MAX. PLATFORM CAPACITY: 800 LBS.
BOOM ROTATION: CONTINUOUS 360 DEGREES
24" X 48" X 42" PLATFORM HYDRAULIC PLATFORM ROTATOR
SINGLE STICK UPPER CONTROL
INDIVIDUAL LOWER CONTROLS
LOWER BOOM CHASSIS INSULATING SYSTEM
HYDRAULIC EXTENSION SYSTEM W/ 2 HOLDING VALVES
OUTER BOOM-STEEL / INNER BOOM-STEEL & FIBERGLASS
NON-LUBE BEARINGS USED AT ALL PIVOT POINTS
OPEN-CENTER HYDRAULIC SYSTEM
2-SPEED MANUAL THROTTLE CONTROL
HYDRAULIC PLATFORM LEVELING IN ALL BOOM POSITIONS
ENGINE START/STOP AT UPPER CONTROLS

CTRAC8000:

VERSATILE, HIGH PAYLOAD, LOW GROUND PRESSURE TRACK VEHICLE
SPECIALLY DESIGNED TO DELIVER TODAY'S GENERATION OF HIGH CAPACITY CRANES &
LONG-REACHING PLATFORMS TO THOSE JOBSITES YOU CAN'T REACH ON RUBBER TIRES.

ITS UNIVERSAL CHASSIS DESIGN MAKES FOR EASY MOUNTING AND DISMOUNTING BETWEEN EQUIPMENT.

THE CRANE OR LIFT MOUNTED TO THE CTRAC8000 WILL SEE NO CHANGE IN THE STANDARD LIFT CAPACITIES, CHARTS OR RANGE DIAGRAMS.

THERE ARE NO MODIFICATIONS TO THE OUTRIGGERS OR CRITICAL COMPONENTS, MAINTAINING THE MANUFACTURER'S WARRANTY.

STANDARD TIER 4 CUMMINS ENGINE IS COMPLIANT WITH ALL US EMISSIONS STANDARDS.

EXPORT ENGINES AVAILABLE.

DUAL BOGIE WHEELS MAXIMIZE STABILITY, MAINTAIN EVEN GROUND PRESSURE & IMPROVE LATERAL STABILITY.
ACCEPTS ANY CRANE/AERIAL DEVICE/TRUCK-MOUNTED EQUIPMENT REQUIRING AN 80K GVWR CHASSIS.



888-925-0858
www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

