



VERSALIFT VST-9500-MHI BUCKET TRUCK

99' ARTICULATING TELESCOPIC MATERIAL HANDLING AERIAL DEVICE



SPECS

HORIZONTAL REACH: 61'8"

WORKING HEIGHT: 99'10"

STOWED TRAVEL HEIGHT: 12'5"

MAX PLATFORM CAPACITY: 600 LBS. / 500 LBS. W/ OPT. JIB

OPT. LOWER BOOM LIFE EYE CAPACITY: 1,500 LBS.

HEIGHT TO BOTTOM OF PLATFORM: 94'9"

OUTER/INNER BOOM TRAVEL: -25 TO +75 DEGREES

LOWER BOOM TRAVEL: 0 TO +88 DEGREES

INNER BOOM EXTENSION: 256"

ROTATION: 360 DEGREES CONTINUOUS

OPERATING PRESSURE: 3,000 PSI

FLOW RATE: 10 GPM

10 MICRON RETURN / 100 MESH SUCTION

OPEN CENTER HYDRAULIC SYSTEM

PTO PUMP POWER SOURCE

UPPER BOOM INSULATION GAP: 52"

LOWER BOOM INSULATION GAP: 24"

ENGINE START & STOP FROM PLATFORM & LOWER CONTROLS

SINGLE STICK CONTROL

CHASSIS INSULATING SYSTEM

REMOVABLE 1,000 LB. MH WINCH & JIB

CLOSED HEAVY-DUTY 24" X 48" PLATFORM

90 DEGREES PLATFORM ROTATOR & GROUND ACCESS

DUAL RADIAL OUTRIGGERS W/ INTERLOCK



888-925-0858

www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

